WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 88464
Permit No.
Basin 230

NOTICE OF INTENT NO. 21662

1. OWNER Phillip Schulz
MAILING ADDRESS H.C. 69, Box 443X
Amargosa Valley Nv. 89020
ADDRESS AT WELL LOCATION Charity St.
Amargosa Valley Nv. 89020

2. LOCATION SE ¼ SW ¼ Sec. 35 T. 16 N/S R. 49 E. NYE County
PERMIT NO. (Issued by Water Resources) 19-631-27 (Parcel No.) (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☒ Other Mud

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
gravel w/snd.		0	50	50
Kalcachy		50	57	7
tan clay		57	72	15
limestone		72	80	8
tan clay		80	96	16
limestone		96	104	8
snd		104	120	16
limestone		120	125	5
gravel	1st	125	140	15
gravel w/snd.		140	170	30
wt. clay w/gravel layers		170	200	30
limestone		200	205	5
snd.		205	213	8
gravel	2nd	213	218	5
wt. cly.		218	228	10
limestone		228	232	4
Bottom of Well			232	

DCNR/DWR
RECEIVED
APR 07 2003
LAS VEGAS OFFICE

Date started 3/28/03, 19__
Date completed 4/01/03, 19__

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 232 Feet Depth Cased 232 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
12¼ Inches		0 Feet	232 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8"	Steel	.188	0	232

Perforations:
Type perforation Machined
Size perforation 3/16" X 3" X 12" - 6 row
From 110 feet to 131 feet
From 191 feet to 212 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50'
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☒ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 232 feet

9. WATER LEVEL
Static water level 108 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Cook Drilling Co. (Contractor)
Address HCR 70, Box 543 (Contractor)
Amargosa Valley, Nv.
Nevada contractor's license number issued by the State Contractor's Board 5376-A
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2160
Signed [signature] (By driller performing actual drilling on site or contractor)
Date 4/2/03

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627