WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 88597
Permit No.
Basin 069

NOTICE OF INTENT NO. 44281

1. OWNER WINNEMUCCA FARMS
MAILING ADDRESS 1 POTATOE PLACE
WINNEMUCCA, NV 89445
ADDRESS AT WELL LOCATION WINNEMUCCA FARMS NORTH END

2. LOCATION SE ¼ SE ¼ Sec. 36 T. 39 N/S R. 38 E. HUMBOLDT County

PERMIT NO. 30344 (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
☐ New Well ☒ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☒ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other REVERSE

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
TOP SOIL		0	6	6
HARD BURNT CLAY		6	50	44
COARSE SAND, PEA GRAVEL		50	162	112
SAND, CLAY MIX		162	177	15
FINE-COARSE SAND		177	186	9
BRN CLAY		186	198	12
SAND, CLAY		198	203	5
FINE-COARSE SAND		203	212	9
BRN CLAY		212	224	12
FINE-COARSE SAND, CLAY LAYERS		224	274	50
BRN CLAY		274	321	47
FINE-COARSE SAND, CLAY LAYERS		321	383	62
BRN CLAY, SANDSTONE		383	562	179
SAND, PEA GRAVEL CLAY LAYERS		562	616	54
BRN CLAY, SAND MIX		616	656	40
SAND, GRAVEL, CLAY MIX		656	790	134
BRN + GREEN CLAY		790	830	40
SAND, GRAVEL, CLAY		830	892	62
BRN CLAY		892	950	58
FINE-MED SAND, GRAVEL		950	954	4
GREEN SANDY CLAY		954	960	12

Date started JULY 15, 2002
Date completed JULY 23, 2002

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☒ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
1353	271	2 hrs

8. WELL CONSTRUCTION
Depth Drilled ____ Feet Depth Cased ____ Feet

HOLE DIAMETER (BIT SIZE)

		From	To
28 Inches		0 Feet	960 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
18"		.375	+2	960
EXCEPT WHERE WIRE WRAP SCREENS ARE LOCATED LISTED BELOW				

Perforations:
Type perforation 18" JOHNSON WIRE WRAP SCREENS
Size perforation SLOT SIZE .040
From 340 feet to 380 feet
From 460 feet to 500 feet
From 560 feet to 620 feet
From 640 feet to 800 feet
From 840 feet to 920 feet
940 960

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50'
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☒ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 960 feet

9. WATER LEVEL
Static water level 85 feet below land surface
Artesian flow ____ G.P.M. ____ P.S.I.
Water temperature 70 °F Quality GOOD

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name RIVERSIDE, INC (Contractor)
Address PO BOX 720 (Contractor)
PARMA, ID 83660
Nevada contractor's license number issued by the State Contractor's Board 0044881
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1919
Signed [signature] (By driller performing actual drilling on-site or contractor)
Date 7-30-02

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627