WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 88738
Permit No.
Basin 107

NOTICE OF INTENT NO. 47905

1. OWNER Jerry Olson
MAILING ADDRESS PO. Box 25 Wellington Nev 89444
ADDRESS AT WELL LOCATION Lodge Drive Wellington Nevada 89444
2. LOCATION B E ¼ S E ¼ Sec. 12 T. 17 N/S R. 23 E. Lyon County
PERMIT NO. Issued by Water Resources
09-132-01 Parcel No.
Lodge Poll Estates Subdivision Name

3. WORK PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☑ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☑ Cable ☐ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
D.D. top soil		0	10	10
hard Pan		10	15	5
sandy brown clay		15	40	25
brown clay		40	50	10
brown sandy clay		50	85	35
coarse shell	yes	85	92	7
fine + coarse sand	yes	92	115	23
gray fine sand	yes	115	145	30
gray clay		145	195	50
Hard gray clay		195	210	15
sandy gray clay		210	235	25
sandy brown clay		235	255	20
brown clay + sand	yes	255	280	25
coarse sand + gravel	yes	280	320	50
blue gray clay		320	325	5

RECEIVED
03 JAN -8 AM 11:06
STATE ENGINEER'S OFFICE

Date started Dec 8 -02, 19
Date completed Jan 4 -03, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☑ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
60	100	12 hrs

8. WELL CONSTRUCTION
Depth Drilled 325 Feet Depth Cased 320 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
12 Inches		0 Feet	55 Feet
8 Inches		55 Feet	320 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8 5/8		188	0	320

Perforations:
Type perforation Factory Saw Slott
Size perforation 3/32 X 3
From 290 feet to 320 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 50
Placement Method: ☐ Pumped ☑ Poured
Seal Type: ☑ Neat Cement ☑ Cement Grout ☐ Concrete Grout
Gravel Packed: ☐ Yes ☑ No
From feet to feet

9. WATER LEVEL
Static water level 100 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature Cold °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Edmund Miller Drilling (Contractor)
Address PO. Box 92 Smith Nev (Contractor) 89430
Nevada contractor's license number issued by the State Contractor's Board 321664
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 718
Signed Edmund Miller (By driller performing actual drilling on site or contractor)
Date Jan 6 -03
Bill Sutton 2232

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627