WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 88803
Permit No.
Basin 087

NOTICE OF INTENT NO. 48815

1. OWNER Washoe County DWR
MAILING ADDRESS 4930 Energy Way, Reno Nev
ADDRESS AT WELL LOCATION 450 Sunshine, Reno Nev

2. LOCATION SW ¼ SW ¼ Sec. 7 T. 19 N/S R. 20 E. Washoe County
PERMIT NO. W2030040 (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☑ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☑ Other Sonic

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Road Base		0	1.5	1.5
Sand, Gravel + Cobbles		1.5		
To 4"			5	3.5
Sand		5	5.5	.5
Sand, Gravel, + Cobbles		5.5		
To 8			20	14.5
Boulder		20	21	1
Silty Sand, gravel		21		
+ Cobbles To 6"			24	3
Sand + Gravel	yes	24	25	1
Sand, Gravel + Cobbles		25		
To 4"			30	5
Sand	yes	30	31	1
Silty sand + Gravel		31	32	1
Sandy clay		32	35	3
Silt Sand + Gravel		35	36	1
Sand + Cobbles To 3"	yes	36	38	2
Sand Gravel		38	39	1
Silty sand + Gravel +		39		
Cobbles To 4"			46	7
Gravel	yes	46	47	1
Clay + Gravel + Cobbles		47	52	5
To 3"			52	5
Silty Sand + Gravel + Cobbles		52	56	4
Clean sand	yes	56	61	5
Silty Sand + Gravel		61	64	3
Clean sand + Gravel	yes	64	67	3
Silty sand + Gravel		67	70	3

Date started 3/27, 2003
Date completed 3/28, 2003

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 70 Feet Depth Cased 70 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
6 Inches		0 Feet	70 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2		Sch 40 PVC	0	70

Perforations:
Type perforation Slotted
Size perforation .020
From 40 feet to 70 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 38
Placement Method: ☑ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☑ Yes ☐ No
From 38 feet to 70 feet

9. WATER LEVEL
Static water level feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Prosonic Corp (Contractor)
Address 305 E Comstock (Contractor)
Chandler AZ
Nevada contractor's license number issued by the State Contractor's Board 0051765
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1677
Signed J. Dunlap (By driller performing actual drilling on site or contractor)
Date 3/28/03

(Rev. 12-01) USE ADDITIONAL SHEETS IF NECESSARY (O)-627