WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 89234
Permit No.
Basin 104

NOTICE OF INTENT NO. 49509

1. OWNER Silver Oak Dev.
MAILING ADDRESS 3075 College Dr
ADDRESS AT WELL LOCATION Silver Oak Golf Course Fairway 1

2. LOCATION NW ¼ SW ¼ Sec 6 T 15 N/S R 20 E Douglas County
PERMIT NO. (Issued by Water Resources) Parcel No. LOT 2 Subdivision Name Silver Oak ph 4

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other Sonic

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Soils - Small Gravels		0'	5'	5'
Silty Sand		5'	12'	7'
Clay - Brownish - Stiff		12'	16'	4'
Silty Sand - Gray		16'	23'	7'
Sandy Gravel		23'	48'	25'
Sands - Grayish Brown		48'	62'	14'
Sands - Gray - Coarse		62'	75'	13'
Saturated Coarse Sand		75'	110'	35'
Reddish Brown Sand Medium Grained		110'	165'	55'
Clayey Sand		165'	173'	8'
Gravels Small to Medium Sized		173'	178'	5'
Sands - Clay Poorly Sorted		178'	200'	22'
Sands with Clay Seam		200	232'	32'
Sandy Gravel		232'	250	18'

Date started 3-4, 19
Date completed 3-11, 2003

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 250 Feet Depth Cased 250 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
8 Inches		0 Feet	250 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4"	sch 80		0	20

Perforations:
Type perforation Factory
Size perforation .020
From 250 feet to 20' feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 18' - 16 Bentonite chips
Placement Method: ☐ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 250 feet to 18' feet

9. WATER LEVEL
Static water level 28 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Dorset Company Contractor
Address Box 1000 Contractor
Dayton, NV 89403
Nevada contractor's license number issued by the State Contractor's Board 0010157
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-
Signed [signature] By driller performing actual drilling on site or contractor
Date 3/15/03

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627