

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 40353

1. OWNER BOEING NORTH AMERICAN, INC. ADDRESS AT WELL LOCATION Rocketdyne
 MAILING ADDRESS 6633 Canoga Avenue Former NFL-Area D
Canoga Park, California 91309 2555 Whiskey Springs Road, Reno, NV 89510
 2. LOCATION SW $\frac{1}{4}$ SE $\frac{1}{4}$ Sec. 12 T. 22 N N/S R. 21 F. Washoe County
 PERMIT NO. DEX-15 077-110-01 Palomino Valley Unit 1 12-2-1-5
 Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other _____
 4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
 5. WELL TYPE
 Cable Rotary RVC
 Air Other...TUBEX

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Brown gravel-sand-silt mix, cobbles & boulder at surface		0	3	3
Reddish brown clayey sands, moist, fine-coarse subrounded, moderately graded, some fine-coarse gravels		3	13	10
Boulders		13	17	4
Reddish brown gravel-sand-clay mix, saturated, fine-coarse sands, fine-coarse gravels, subrounded-subangular, well graded		17	46	29
Medium brown gravel-sand mix, saturated, fine-coarse sands, fine-coarse gravels, subrounded subangular, well graded, some clay		46	54	8
Boulders		54	57	3
Medium brown gravel-sand mix, saturated, fine-coarse sands, fine-coarse gravels, subrounded subangular, well graded, some clay		57	66	9
Grayish medium rhyolite tuff		66	70	4

8. WELL CONSTRUCTION
 Depth Drilled 70 Feet Depth Cased 70 Feet
 HOLE DIAMETER (BIT SIZE)
 From 10 Inches To 70 Feet
 _____ Inches _____ Feet _____ Feet
 _____ Inches _____ Feet _____ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8 x .188	0-8 ft./stainless steel	8-10 ft.		
6 5/8 x 3/8"	adaptor			
	Welded stainless steel cap	3"		

Perforations:
 Type perforation stainless steel/factory slot
 Size perforation .020 wire wrap
 From 10 feet to 70 feet
 From _____ feet to _____ feet
 From Surface completion 0-4 ft.
 From 4x4x4 open bottom concrete vault
 From with metal lid

Surface Seal: Yes No Seal Type:
 Depth of Seal 4 to 6 ft. Neat Cement
 Placement Method: Pumped Cement Grout
 Poured Concrete Grout
 Bentonite seal: 6-8 ft.
 Gravel Packed: Yes No #30 sand 8-9 ft
 From 9-70 ft. #8 sand Lonestar feet

9. WATER LEVEL
 Static water level 16.36 feet below land surface
 Artesian flow not known G.P.M. _____ P.S.I. _____
 Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name WAYNE DRILLING, INC. Contractor
 Address P.O. BOX 12370 Contractor
RENO, NEVADA 89510
 Nevada contractor's license number 0022549
 issued by the State Contractor's Board
 Nevada driller's license number issued by the 908
 Division of Water Resources, the on-site driller
 Signed [Signature]
 By driller performing actual drilling on site or contractor
 Date June 25, 2002

Date started October 4, 1999, 19____
 Date completed October 5, 1999, 19____

7. WELL TEST DATA

TEST METHOD: <input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
No test			

RECEIVED
 JUL 15 2002
 STATE ENGINEER'S OFFICE