

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 89445
Permit No. 071
Basin _____

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 48635

OWNER Robert Parlasca ADDRESS AT WELL LOCATION south Grass Valley Rd
MAILING ADDRESS 561 Keystone Ave Box 358
Reno, NV 89503
2. LOCATION SE 1/4 NW 1/4 Sec. 11 T 32N N/S R 38 E Pershing County
PERMIT NO. 67741 Issued by Water Resources Parcel No. _____ Subdivision Name _____

3. WORK PERFORMED
 New Well Replace Recondition Deepen Abandon Other _____
4. PROPOSED USE
 Domestic Irrigation Test Municipal/Industrial Monitor Stock
5. WELL TYPE
 Cable Rotary RVC Air Other _____

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
top soil		0	3	3
sand & clay		3	6	3
coarse to fine sand		6	10	4
sand & clay w/s gravel		10	22	12
sand & some gravel		22		
w/clay layers			64	42
sand w/hard clay layers		64	72	8
sand & clay layers		72		
w/cobbles			84	12
sand & clay layers		84	92	8
sandy clay		92	103	11
sand & gravel w/clay		103		
layers			107	4
clay w/sand layers		107	137	30
clay w/sand & gravel		137		
layers			155	18
sand & clay layers w/s		155		
gravel			198	43
clay w/sand layers		198	209	11
clay		209	231	22
sand & clay layers		231	239	8
clay		239	243	4
sand & some gravel		243		
w/clay layers			252	9

8. WELL CONSTRUCTION
Depth Drilled 275 Feet Depth Cased 270 Feet
HOLE DIAMETER (BIT SIZE)
From _____ To _____
9-7/8 inches 0 feet 275 feet
_____ inches _____ feet _____ feet
_____ inches _____ feet _____ feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6-5/8		.188	+2	270

Perforations:
Type perforation mill slot
Size perforation .090
From 150 feet to 190 feet
From 230 feet to 270 feet
From _____ feet to _____ feet
From _____ feet to _____ feet
From _____ feet to _____ feet
Surface Seal: Yes No Seal Type: Neat Cement Cement Grout Concrete Grout
Depth of Seal 50
Placement Method: Pumped Poured
Gravel Packed: Yes No
From 50 feet to 270 feet

9. WATER LEVEL
Static water level 95 feet below land surface
Artesian flow _____ G.P.M. _____ P.S.I.
Water temperature cool °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Humboldt Drilling & Pump Co., Inc. Contractor
Address 4675 W. Winnemucca Blvd Contractor
Winnemucca, Nevada 89445
Nevada contractor's license number issued by the State Contractor's Board 015234
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2158
Signed Jerry A. Tomp
By driller performing actual drilling/on-site or contractor
Date 4/26/03

Date started 4/3/03 . 19
Date completed 4/8/03 . 19

7. WELL TEST DATA

TEST METHOD:	TEST METHOD:	
	G.P.M.	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input checked="" type="checkbox"/> Air Lift		
	Draw Down (Feet Below Static)	
	<u>60-80</u>	<u>2.5 hrs.</u>

RECEIVED
 APR 29 AM 10:30
 STATE ENGINEERS OFFICE

Continued on next page

