WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 90191
Permit No.
Basin 091

NOTICE OF INTENT NO. 18830

1. OWNER Summit Engineering Corp.
MAILING ADDRESS 5405 Mae Anne Ave.
Reno, NV 89523

ADDRESS AT WELL LOCATION Boomtown Hotel and Casino
2200 I-80 West, Verdi, NV

2. LOCATION NE ¼ SE ¼ Sec 16 T 19N N/S R 18 E Washoe County
PERMIT NO. M/O#500 (Issued by Water Resources) BH #3 | 381-200-09 (Parcel No.) | Boomtown, Verdi, NV (Subdivision Name)

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☒ Other S.B.

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☒ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☒ Other Tubex 190

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
10 inches of AC, Gravelly clayey sand, (SC) asplaht grindings moist, dark grey		0	5	5
Tan clayey sand with gravels (SC), clean loose		5	7	2
Sandy gravels (GW) angular to sub-rounded, clean, dry to slightly moist				
Granitic boulders		7	10	3
Tan to brown clayey sands (SC) minor gravels, clean		10	15	5
Gravelly sands (GP) clean, bouldery gravel		15	35	20
Gravelly sands (GP) Clean		35	40	5
Bouldery sands, granitic and basalts, clean		40	45	5
Bouldery sands, basalts and granitics, clean		45	55	10
Basaltic gravels, sandy gravels, clean		55	60	5
Basaltic gravels, sub-angular to subrounded clean		50	65	5

No ground water encountered/Abandoned to surface

Date started 02/06/92, 19
Date completed 02/06/92, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
NO TEST			

8. WELL CONSTRUCTION
Depth Drilled 65 Feet Depth Cased Feet

HOLE DIAMETER (BIT SIZE)

		From	To
9 5/16 Inches		0 Feet	65 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)

SOIL BORING

Perforations:
Type perforation
Size perforation
From feet to feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☐ Yes ☐ No
Depth of Seal
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☐ Yes ☐ No
From feet to feet

9. WATER LEVEL
Static water level DRY feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Wayne Drilling, Inc. (Contractor)
Address P.O. Box 12370 (Contractor)
Reno, NV 89510
Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
Signed Jerry C. Hedman (By driller performing actual drilling on site or contractor)
Date April 15, 1992

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627