WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 90284
Permit No.
Basin 091

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK NEVADA

NOTICE OF INTENT NO. 33019

1. OWNER Raymond P. Hyne
MAILING ADDRESS P.O. Box 1246
VERDI, NEVADA 89439

ADDRESS AT WELL LOCATION
305 RIVERDALE CIRCLE
VERDI NEVADA 89439

2. LOCATION SE ¼ NE ¼ Sec. 7 T. 19N N/S R. 18 E. WASHOE County
PERMIT NO. (Issued by Water Resources) | LOT 6 BLOCK A - 038 6 9302 (Parcel No.) | RIVERDALE ~~DONNER RANCH~~ (Subdivision Name) Subdivision Unit 1

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Plug existing well drilled in 1986 by Paul Williams to 305 and cased w/ 6" casing. Well deepened in 1992 by Wayne Drilling to 480 with drop liner of 5" casing 305' to 480'. Casing perforated and well abandoned May 16, 2002 using Baroid Aquagard. Pumped 42 - 50 lb. bags Baroid Aquagard to plug. Surface seal 6-9 lb. bag Nevada type I-II Cement Neat.				

Date started May 15, 2002, 19
Date completed May 16, 2002, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 480 Feet Depth Cased 480 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
Inches	Feet	Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6"			0	305'
5"			305'	480'

Perforations:
Type perforation
Size perforation
From feet to feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☐ Yes ☐ No
Depth of Seal 6-9 lb
Placement Method: ☒ Pumped ☐ Poured
NEVADA TYPE I-II
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☐ Yes ☐ No
From feet to feet

9. WATER LEVEL
Static water level 195 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Raymond P. Hyne (Contractor)
Address P.O. Box 2490 (Contractor)
WINNEMUCCA, NEVADA 89446
Nevada contractor's license number issued by the State Contractor's Board NCL# 20552
Nevada driller's license number issued by the Division of Water Resources, the on-site driller # 1278
Signed (By driller performing actual drilling on site or contractor)
Date May 17, 2002

(Rev. 3 91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627