


STATE OF NEVADA  
 DIVISION OF WATER RESOURCES  
**WELL DRILLER'S REPORT**

OFFICE USE ONLY  
 Log No. 90581  
 Permit No. 55186  
 Basin 59



PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

Please complete this form in its entirety in  
 accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. **49276**

1. OWNER Newmont Mining Corporation DW-5 ADDRESS AT WELL LOCATION McCoy/Cove minesite,  
 MAILING ADDRESS P.O. Box 669 south of Battle Mountain, NV  
Carlin, NV 89822

2. LOCATION SW 1/4 SE 1/4 Sec. 36 T 29N N/S R 42 E Lander County  
 PERMIT NO. 55186 Issued by Water Resources Parcel No. N/A Subdivision Name N/A

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other \_\_\_\_\_

4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other \_\_\_\_\_

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Abandoned by pumping abantonite via tremmie from 1030' to 686'. Pumped neat cement and tagged at 726', pumped abantonite to 409', where it would rise no further. Pumped bentonite cement to 102', poured SAG mill reject to 20' and capped with concrete grout.				
Quantities Used:				
Concrete: 43.6 cu.ft.				
SAG reject: 163.7 cu.ft.				
Bentonite cement: 4889 cu.ft.				
Abantonite: 1002.75 cu.ft.				
Cement: 99.2 cu.ft.				
Abantonite: 2841.13 cu.ft.				

8. WELL CONSTRUCTION  
 Depth Drilled 1060 Feet Depth Cased 1040 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From	To	Feet	Feet
<u>31</u>	<u>0</u>	<u>38</u>		
<u>25</u>	<u>38</u>	<u>1060</u>		

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>26</u>	<u>102</u>	<u>0.375</u>	<u>0</u>	<u>38</u>
<u>20</u>	<u>78.6</u>	<u>0.375</u>	<u>+1</u>	<u>1040</u>

Perforations:  
 Type perforation Wire Wrap  
 Size perforation 0.125"

From	To	Feet	Feet
<u>560</u>	<u>1040</u>		

Surface Seal:  Yes  No Seal Type:  Neat Cement  
 Depth of Seal 393'  Cement Grout  
 Placement Method:  Pumped  Concrete Grout  
 Poured

Gravel Packed:  Yes  No  
 From 393 feet to 1060 feet

9. WATER LEVEL  
 Static water level 364 feet below land surface  
 Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
 Water temperature \_\_\_\_\_ °F Quality \_\_\_\_\_

Date started 7/26/2003 . 19  
 Date completed 8/4/2003 . 19

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Lang Exploratory Drilling Contractor  
 Address P.O. Box 5279 Contractor  
Elko, NV 89802-5279  
 Nevada contractor's license number issued by the State Contractor's Board 0021976  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2085-T1

Signed Daryl Langman  
 By driller performing actual drilling on-site or contractor  
 Date 8/7/03

B. ST. L