


STATE OF NEVADA
 DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
 Log No. 90583
 Permit No. 57516T
 Basin 059



PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

Please complete this form in its entirety in
 accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. **49278**

1. OWNER **Newmont Mining Corporation** **DW#81** ADDRESS AT WELL LOCATION **McCoy/Cove minesite,**
 MAILING ADDRESS **P.O. Box 669** **south of Battle Mountain, NV**
Carlin, NV 89822

2. LOCATION **NE** 1/4 **SE** 1/4 Sec. **36** T **29N** N/S R **42E** E **Lander** County
 PERMIT NO. **57516T** Parcel No. **N/A** Subdivision Name **N/A**
Issued by Water Resources

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other

4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Abandoned by pumping abantonite via tremie with several lifts of neat cement to overcome apparent dilution problems; then cement followed by SAG reject rock and capped with 20' of cement.				
Quantities Used:				
Cement		0	20	
SAG mill reject rock: 486 cu.ft.		20	176	
Bentonite cement: 680 cu.ft.		176	485	
Cement: 32.2 cu.ft.		485	512	
Abantonite: 172.8 cu.ft.		512	600	
Cement: 92.9 cu.ft.		600	615	
Abantonite: 2005.2 cu.ft.		615	1040	
Cement: 92.9 cu.ft.		1040	1050	
Abantonite: 1002.6 cu.ft.		1050	1175	
Cement: 594 cu.ft.		1175	1420	
Abantonite: 1336.8 cu.ft.		1420	1500	

RECEIVED
 03 JUL 21 AM 11:12
 STATE ENGINEERS OFFICE

Date started 4/7/2003 .19
 Date completed 4/11/2003 .19

7. WELL TEST DATA

TEST METHOD:	Bailer	Pump	Air Lift
G.P.M.	Draw Down (Feet Below Static)	Time (Hours)	

8. WELL CONSTRUCTION

Depth Drilled 1500 Feet Depth Cased 1500 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From	Feet	To	Feet
30	0		40	
20	0		1500	

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
36	145	0.375	+2	38
20	78	0.375	+2	1500

Perforations:

Type perforation Wire Wrap
 Size perforation 0.125"

From	feet to	feet
740	800	800
840	960	960
1000	1100	1100
1140	1460	1460

Surface Seal: Yes No
 Depth of Seal 65'
 Placement Method: Pumped Poured
 Seal Type: Neat Cement Cement Grout Concrete Grout
 Gravel Packed: Yes No
 From 65 feet to 1500 feet

9. WATER LEVEL
 Static water level 440 feet below land surface
 Artesian flow N/A G.P.M. _____ P.S.I. _____
 Water temperature _____ °F Quality _____

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name Lang Exploratory Drilling Contractor
 Address P.O. Box 5279 Contractor
Elko, NV 89802-5279
 Nevada contractor's license number issued by the State Contractor's Board 0021976
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2085-T1
 Signed Daryl Langman
 By driller performing actual drilling on-site or contractor
 Date 7/16/03

B.S.T.C