

OFFICE USE ONLY
 Log No. 92785
 Permit No. _____
 Basin. 084

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 48423

1. OWNER DAVID & LINDA FRITSCH ADDRESS AT WELL LOCATION 3755 Bacon Rind Road
 MAILING ADDRESS 3755 Bacon Rind Road 3755 Bacon Rind Road
Reno, Nevada 89510 Reno, Nevada 89510

2. LOCATION SE 1/4 NE 1/4 Sec. 36 T 22N N/S R 20 E Washoe County Washoe
 PERMIT NO. 076-171-15 Palomino Valley
 Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other

4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Top soil		0	1	1
Brown sandy clay		1	19	18
Soft zone		19	21	2
Brown sandy clays		21	73	52
Soft zone		73	76	3
Brown sandy clay		76	180	104
Soft sandy clays with decomposed granite		180	221	41
Weathered granite		221	281	60
Soft weathered granite rusty		281	312	31
Hard weathered granite		312	335	23
Rusty soft granite (NO WATER)		335	341	6
Hard weathered granite		341	389	48
Fractured granite	X	389	401	12
White granite with quartz		401	416	15
Fracture	X	416	418	2
White granite with quartz		418	426	18

8. WELL CONSTRUCTION
 Depth Drilled 426 Feet Depth Cased 426 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
10 Inches	0 Feet	50 Feet
8 5/8 Inches	50 Feet	322 Feet
6 1/8 Inches	322 Feet	426 Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	0	322
5"OD		.188	302	426

Perforations: factory sawed slot
 Type perforation _____
 Size perforation 3/32 x 3 x 5 around

From 277 feet to 317 feet
 From 382 feet to 422 feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet

Surface Seal: Yes No Seal Type: Neat Cement
 Depth of Seal 50 feet Cement Grout
 Placement Method: Pumped Poured Concrete Grout

Gravel Packed: Yes No
 From 50 feet to 322 feet

9. WATER LEVEL
 Static water level 160 feet below land surface
 Artesian flow _____ G.P.M. _____ P.S.I.
 Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.

Name WAYNE DRILLING, INC. Contractor
 Address P.O. BOX 12370 Contractor
RENO, NEVADA 89510

Nevada contractor's license number 0022549
 issued by the State Contractor's Board

Nevada driller's license number issued by the 923
 Division of Water Resources, the on-site driller

Signed [Signature]
 By driller performing actual drilling on site or contractor

Date July 17, 2003

Date started June 30, 2003, 19_____
 Date completed July 15, 2003, 19_____

7. WELL TEST DATA

TEST METHOD: Bailer Pump Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<u>20+</u>		

RECEIVED
 03 JUL 28 AM 11:17
 STATE ENGINEERS OFFICE