

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

Permit No. 084  
 Basin

NOTICE OF INTENT NO. 40352

1. OWNER BOEING NORTH AMERICAN, INC. ADDRESS AT WELL LOCATION Rocketdyne  
 MAILING ADDRESS 6633 Canoga Avenue Former NFL-Area D  
 Canoga Park, California 91309 Whiskey Springs Road, Reno, NV 89510  
 2. LOCATION SE 1/4 SW 1/4 Sec 7 T. 22N N/S R. 22 E Washoe County  
 PERMIT NO. DEX-11 077-110-12 Palomino Valley  
 Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other

4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other TUBE

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Medium brown gravel-sand-silt mix, dry, boulders, cobbles at surface		0	2	2
Reddish brown gravel-sand mix		2	9	7
Boulder		9	11	3
Reddish brown gravel-sand-clay mix, water added, fine-coarse sand, fine coarse gravel subrounded-subangular, well graded		11	22	11
Boulder		22	24	2
Same as above+some clay		24	56	32
Boulder		56	57	1
Medium brown gravel-sand mix, water added very little water at total depth		57	61	3
Greyish red rhyolite tuff		61	62	1

ABANDON WELL, LOW FLOW.  
 Call Matt Dillon @DWR, Darryl Avela @WCo  
 OK to cement bore hole.  
 Materials used:  
 29 sacks Portland Cement Type II  
 Location: 200 ft Nof Whiskey Springs Road \*  
 400 ft Wof Whiskey Springs Road  
 \* 100 ft Nof DEX-12 (approx.)

8. WELL CONSTRUCTION  
 Depth Drilled \_\_\_\_\_ Feet Depth Cased \_\_\_\_\_ Feet

HOLE DIAMETER (BIT SIZE)  
 From \_\_\_\_\_ To \_\_\_\_\_  
 Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
 Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
 Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)

Perforations:  
 Type perforation \_\_\_\_\_  
 Size perforation \_\_\_\_\_  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  
 Neat Cement  
 Cement Grout  
 Concrete Grout

Placement Method:  Pumped  
 Poured

Gravel Packed:  Yes  No  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet

7. WELL TEST DATA

TEST METHOD:  Bailer  Pump  Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
No test		

Date started October 13, 1999, 19\_\_\_\_\_  
 Date completed October 13, 1999, 19\_\_\_\_\_

9. WATER LEVEL  
 Static water level 60.72 feet below land surface  
 Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
 Water temperature \_\_\_\_\_ °F Quality \_\_\_\_\_

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name WAYNE DRILLING, INC. Contractor  
 Address P.O. BOX 12370 Contractor  
 RENO, NEVADA 89510  
 Nevada contractor's license number 0022549 issued by the State Contractor's Board  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908  
 Signed \_\_\_\_\_ By driller performing actual drilling on site or contractor  
 Date June 22, 2002

RECEIVED  
 JUL 15 2002  
 STATE ENGINEER'S OFFICE