WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 90908
Permit No. 57224
Basin 061

NOTICE OF INTENT NO. 52558

1. OWNER Barrick Goldstrike Mines BW-12
MAILING ADDRESS P.O. Box 29
Elko, NV 89803

ADDRESS AT WELL LOCATION Barrick Goldstrike minesite, north of Carlin, NV.

2. LOCATION NE 1/4 SW 1/4 Sec. 24 T 36N N/S R 49 E Eureka County
PERMIT NO. 57224 (Issued by Water Resources) | N/A (Parcel No.) | N/A (Subdivision Name)

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☒ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Abandoned by pumping abantonite via tremie from T.D. to 1620', where it would rise no further. Poured hole plug while pumping abantonite to 678'. Placed a cement bridge plug from 678' to 662', then poured clean fill to 20', and capped with neat cement.				
Note: This well will be mined off to about 1267' depth.				
Quantities Used:				
Cement: 44 cu.ft.				
Fill: 1400 cu.ft.				
Cement: 41 cu.ft.				
Hole plug: 1890 cu.ft.				
Abantonite: 1946 cu.ft.				

Date started 10/10/2003, 19__
Date completed 10/12/2003, 19__

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 2148 Feet Depth Cased 2144 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
38	Inches	0	Feet	50	Feet
30	Inches	50	Feet	1650	Feet
19	Inches	1650	Feet	2148	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
34	134.70	0.3750	0	50
20	65.70	0.3125	0	1581
16.5	52.27	0.3125	1581	2144

Perforations:
Type perforation Louver
Size perforation 0.125"
From 740 feet to 1581 feet
From 1581 feet to 2144 feet
From ___ feet to ___ feet
From ___ feet to ___ feet
From ___ feet to ___ feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50'
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout
Gravel Packed: ☒ Yes ☐ No
From 50 feet to 1650 feet

9. WATER LEVEL
Static water level 1860 feet below land surface
Artesian flow ___ G.P.M. ___ P.S.I.
Water temperature ___ °F Quality ___

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Lang Exploratory Drilling (Contractor)
Address P.O. Box 5279 (Contractor)
Elko, NV 89802-5279
Nevada contractor's license number issued by the State Contractor's Board 0021976
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2144
Signed Paul Stoddard (By driller performing actual drilling on-site or contractor)
Date 10/23/03

USE ADDITIONAL SHEETS IF NECESSARY

B.ST.L