WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 91177
Permit No.
Basin 212

NOTICE OF INTENT NO. 49416

1. OWNER Contin Const.
MAILING ADDRESS P.O Box 97739
Las Vegas, NV 89193

ADDRESS AT WELL LOCATION Magic Way – Las Vegas Wash

2. LOCATION NE ¼ NE ¼ Sec. 28 T. 21S N/S R. 63 E. Clark County
PERMIT NO. DW-1166 (Issued by Water Resources) 160-28-510-006 (Parcel No.) Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE Temp. Dewatering.
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other Bucket Auger

6. LITHOLOGIC LOG

	Material	Water Strata	From	To	Thickness
Well #1	Sand, Clay		0	12	12
	Poorly Graded Sand/Gravel		12	21	9
	Silty Sand		21	26	5
	Silty Sands with Gravel		26	28	2
	Sands and Gravel		28	30	2
	Coarse Sands and Gravel		30	38	8
	Clay with Gravel & Cobbles		38	40	2
Well #2	Same as #1				
Well #3	Same as #1				
Well #4	Sandy Clay		0	10	
	Poorly Graded Sand with Silts		10'	15'	
	Silty Sands with Gravel		15'	17'	
	Fine Silty Sand, Stiff		17'	27'	
	Silty Sand with Gravel		27'	37'	
	Clay		37'	40'	
Well #5	Same as #4				

DCNR/DWR
RECEIVED
SEP 19 2003
LAS VEGAS OFFICE

Date started 8-28-03, 19
Date completed 8-28-03, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 40 Feet Depth Cased 40' Feet

HOLE DIAMETER (BIT SIZE)

	From	To
24" Inches	0 Feet	40' Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8"	PVC	Sch-40	0'	20'

Perforations:
Type perforation Saw Cut
Size perforation .032
From 20' feet to 40' feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☐ Yes ☒ No
Depth of Seal
Placement Method: ☐ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 0 feet to 40' feet

9. WATER LEVEL
Static water level 7 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature Cool °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Griffith Dewatering (Contractor)
Address 536 E. Maitland St. (Contractor)
Ontario CA 91761
Nevada contractor's license number issued by the State Contractor's Board 0031246
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-1985
Signed (By driller performing actual drilling on site or contractor)
Date 8-28-03

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627