WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

# WELL DRILLER'S REPORT

**Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340**

OFFICE USE ONLY
Log No. 91348
Permit No.
Basin 212

NOTICE OF INTENT NO. 22650

1. OWNER Control Const.
MAILING ADDRESS 1720 E. Lake Mead Dr. Henderson
ADDRESS AT WELL LOCATION Vegas Valley + Hadleywood

2. LOCATION NW ¼ SW ¼ Sec. 14 T. 21 N/S R. 62 E County
PERMIT NO. DW 1170 (Issued by Water Resources) 161-14-339-001 (Parcel No.) Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE Temp Dewatering
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☐ Other Bucket Auger

6. LITHOLOGIC LOG

| | Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|---|
| Well #1 | Dry Clays + Silts | | 0 | 14' | |
| | Silty Sands | | 14' | 18' | |
| | Silty Clays | | 18' | 26' | |
| | Clay | | 26' | 35' | |
| Well #2 | Same as #1 | | | | |
| Well #3 | Dry Clays + Silts | | 0' | 14' | |
| | Silty Sands | | 14' | 18' | |
| | Silty Clays | | 18' | 24' | |
| | Silty Sands + Gravel | | 24' | 26' | |
| | Clay | | 26 | 35' | |

Date started 11-12-03, 20
Date completed 11-12-03, 20

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|
| | | |

8. WELL CONSTRUCTION
Depth Drilled 35' Feet Depth Cased 35' Feet

HOLE DIAMETER (BIT SIZE)

| Inches | From (Feet) | To (Feet) |
|---|---|---|
| 24" | 0 | 35' |
| | | |
| | | |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 6" | PVC | Sch-40 | 0 | 15' |
| | | | | |

Perforations:
Type perforation Saw Cut
Size perforation .032
From 15 feet to 35' feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☐ Yes ☒ No
Depth of Seal
Placement Method: ☐ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 0 feet to 35' feet

9. WATER LEVEL
Static water level 14' feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature Cool °F Quality Good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Griffith Dewatering (Contractor)
Address 536 E. Maitland St. (Contractor)
Ontario CA 91761
Nevada contractor's license number issued by the State Contractor's Board 0031246
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-1985
Signed (By driller performing actual drilling on site or contractor)
Date 11-12-03

(Rev. 12-01) USE ADDITIONAL SHEETS IF NECESSARY (O)-627