WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 91494
Permit No.
Basin 212

NOTICE OF INTENT NO. 74909

1. OWNER The Esslinger Family Trust
MAILING ADDRESS 12932 N. 136th St
Scottsdale, AZ 85259
ADDRESS AT WELL LOCATION 5525 W Charleston
Las Vegas NV

2. LOCATION NE ¼ NW ¼ Sec. 1 T. 21 N/S R 60 E Clark County

PERMIT NO. (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other Auger

6. MW-113 LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Fill		.5'	6'	5.5
Sand, reddish brown w/course gravel		6'	13'	7
sandy clay, reddish brown, dry		13'	21'	8
silty sand, w/clay, course gravel		21'	27'	6
silty clay brown w/gravel		27'	38'	11
caliche		38'	52'	14
silty clay, slight odor		52'	78'	26

Date started Sep 15, 1903
Date completed Sep 15, 1903

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 75 Feet / Depth Cased 75 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
9 Inches	75 Feet	75 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4.5	PVC	Sch 40	0	75

Perforations:
Type perforation Factory Slot
Size perforation .020
From 45 feet to 75 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 40 to surface
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 40 feet to 75 feet

9. WATER LEVEL
Static water level 63 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name (Contractor) Elite Drilling Inc
Address (Contractor) 5115 S. Industrial Rd #104
Las Vegas, NV 89118
Nevada contractor's license number issued by the State Contractor's Board 0054931
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-1869
Signed (By driller performing actual drilling on site or contractor)
Date 11-12-03

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 91499
Permit No.
Basin 212

NOTICE OF INTENT NO. 24909

1. OWNER The Esslinger Family Trust
MAILING ADDRESS 12932 N. 136th St
Scottsdale, AZ 85259

ADDRESS AT WELL LOCATION 5525 W Charleston
Las Vegas NV

2. LOCATION NE ¼ NW ¼ Sec. 1 T. 21 N/S R. 60 E. Clark County

PERMIT NO. (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other Auger

6. MW-113 LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Fill		0'	6'	5.5
sand, reddish brown w/course gravel		6'	13'	7
sandy clay, reddish brown, dry		13'	21'	8
silty sand, w/clay, course gravel		21'	27'	6
silty clay brown w/gravel		27'	38'	11
caliche		38'	52'	14
silty clay, slight odor		52'	78'	26

Date started Sep 15, 1903
Date completed Sep 15, 1903

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 75 Feet / Depth Cased 75 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From Feet	To Feet
9	75	75

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4.5	DVC	Sch 40	0	75

Perforations:
Type perforation Factory Slot
Size perforation .020
From 45 feet to 75 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 40 to surface
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 40 feet to 75 feet

9. WATER LEVEL
Static water level 63 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Elite Drilling Inc (Contractor)
Address 5155 S. Industrial Rd #104 (Contractor)
Las Vegas, NV 89118
Nevada contractor's license number issued by the State Contractor's Board 0054931
Nevada driller's license number issued by the Division of Water Resources, ~~the on-site driller~~ M-1809
Signed (By driller performing actual drilling on site or contractor)
Date 11-12-03

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627