WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 91584
Permit No.
Basin 212

NOTICE OF INTENT NO. 25549

1. OWNER Distintive Homes Toas Estates 111 (Toas)
MAILING ADDRESS
ADDRESS AT WELL LOCATION 7070 W Rio Vista

2. LOCATION NW ¼ NE ¼ Sec. 27 T 19S N/S R 60 E Clark County
PERMIT NO. (Issued by Water Resources) Parcel No. 125-27-503-013 Subdivision Name

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
NAC 534-420 Section 8				
A. Depth of Well - 400 Ft.				
B. The depth to which the materials used to plug the well were placed - 400Ft.				
C. The type, size * Location of perforations which were made in the casing:				
Type: Knife (Rotary)				
Size: 1/4" x 1 1/2"				
Location: 400 ft. up to 70 Ft.				
D. The debris encountered: None				
E. Materials used to plug the well:				
25 Sack cement slurry				
Materials slips attached.				
Section 9:				
Neat cement by tremie pipe in an upward direction.				

Date started 12/24/03, 19
Date completed 12/27/03, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled ____ Feet Depth Cased ____ Feet

HOLE DIAMETER (BIT SIZE)

	From	To
Inches	Feet	Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)

Perforations:
Type perforation
Size perforation
From feet to feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☐ Yes ☐ No
Depth of Seal
Placement Method: ☐ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☐ Concrete Grout
Gravel Packed: ☐ Yes ☐ No
From feet to feet

9. WATER LEVEL
Static water level 120 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Vernon H. Dimick (Contractor)
Address 5360 N. Bonita Vista St. (Contractor)
Las Vegas, Nev. 89149
Nevada contractor's license number issued by the State Contractor's Board 10062
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 552
Signed V.H. Dimick (By driller performing actual drilling on site or contractor)
Date 12-29-03

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627