WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 9160604
Permit No.
Basin 073

NOTICE OF INTENT NO. 48613

1. OWNER Vince Shearer
MAILING ADDRESS 1900 Old Imigrant Rd
Lovelock, NV 89419

ADDRESS AT WELL LOCATION Lot 31 1480 Horseshoe

2. LOCATION SW 1/4 NW 1/4 Sec. 36 T 28N N/S R 31E E Pershing County
PERMIT NO. (Issued by Water Resources) 003-513-03 (Parcel No.) Diamond S Ranch Estates (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
clay		0	25	
sand		25	35	10
black clay		35	90	55
sand		90	100	10
sand & clay		100	110	10
green clay		110	200	90
sand		200	240	40

RECEIVED 03 MAY 21 AM 11:23 STATE ENGINEERS OFFICE

Date started 5/14/03, 19__
Date completed 5/16/03, 19__

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
15		6 hrs

8. WELL CONSTRUCTION
Depth Drilled 240 Feet Depth Cased 240 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
11 inches		0 Feet	240 Feet
inches		Feet	Feet
inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6-5/8		.188	+1	~~200~~ 240

Perforations:
Type perforation mill slot
Size perforation .90
From 200 feet to 240 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 60
Placement Method: [X] Pumped [ ] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 60 feet to 240 feet

9. WATER LEVEL
Static water level 1 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature cool °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Humboldt Drilling & Pump Co., Inc. (Contractor)
Address 4675 W. Winnemucca Blvd (Contractor)
Winnemucca, Nevada 89445
Nevada contractor's license number issued by the State Contractor's Board 015234
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1713
Signed [signature] (By driller performing actual drilling on-site or contractor)
Date 5/20/03