WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 91722
Permit No.
Basin 103

NOTICE OF INTENT NO. 46642

1. OWNER Jim & Jennifer Renth
MAILING ADDRESS 270 Imperial Road
Dayton, NV 89403

ADDRESS AT WELL LOCATION 270 Imperial Road
Dayton,Nevada-89403

2. LOCATION NW 1/4 NE 1/4 Sec. 9 T 16N N/S R 22E E Lyon County
PERMIT NO. (Issued by Water Resources) 19-141-08 (Parcel No.) (Subdivision Name)

3. WORK PERFORMED
[X] New Well [X] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [ ] RVC
[ ] Air [X] Other Mud

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sand		0	13	13
Clay		13	20	7
Sand & Gravel		20	53	33
Sand		53	87	34
Clay		87	101	14
Broken Rock		101	132	31
Clay		132	156	24
sand & Gravel	x	156	182	26
Broken Rock	x	182	198	16
Total Depth		198		

RECEIVED 03 JUN 13 AM 10:57 STATE ENGINEER'S OFFICE

Date started 05/16/2003 , 19__
Date completed 05/23/2003 , 19__

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
10	80	1 hour
20	100	1 hour
30+	140	1 hour
30+	180	1 Hour

8. WELL CONSTRUCTION
Depth Drilled 198 Feet Depth Cased 198 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10-5/8 Inches		0 Feet	198 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6-5/8	12.9	.188	+2	198

Perforations:
Type perforation Factory Sawed
Size perforation 3/32 x 3
From 178 feet to 198 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50
Placement Method: [X] Pumped [ ] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout
Gravel Packed: [X] Yes [ ] No
From 50 feet to 198 feet

9. WATER LEVEL
Static water level 60 feet below land surface
Artesian flow G.P.M. P.S.I
Water temperature cool °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name A.S.A.P. Pump & Well Service (Contractor)
Address P.O. Box 60130 (Contractor)
Reno,Nevada 89506
Nevada contractor's license number issued by the State Contractor's Board 35387-B
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2121
Signed Larry Welch (By driller performing actual drilling on-site or contractor)
Date 06/16/2003

USE ADDITIONAL SHEETS IF NECESSARY