WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

I

OFFICE USE ONLY
Log No. 91835
Permit No.
Basin 103

NOTICE OF INTENT NO. 42237

1. OWNER McQueary Excavating
MAILING ADDRESS P.O. Box 1841
Carson City, NV 89702

ADDRESS AT WELL LOCATION 1/4 mile east of Cardelli Lane and River Road near Dayton, NV.

2. LOCATION SW 1/4 SW 1/4 Sec. 33 T 17N N/S R 22E E Lyon County
PERMIT NO. ~~63626~~ (13402)
Issued by Water Resources | Parcel No. | Subdivision Name

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic (☒ Irrigation) ☐ Test
~~☒ Municipal/Industrial~~ ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Removed 185' of turbine pump. Measured water level at16'. Measured depth of well at 379'. Attempted to bail debris from well and reached depth of 385' and hit hard bottom. Installed 14" Mills Knife and perforated blank casing from 100' back to surface. The following day, we installed 378' of 2" tremme pipe and pumped in 18 cubic yards of neat cement. Well was 14" casing from 0 to 300' and 10" casing from 300' to 400'. Well volume shaoul have required approximately 15 cubic yards of cement. (original log attached)				
Plugging of log 1620				

RECEIVED
03 JUN 24 AM 10:38
STATE ENGINEERS OFFICE

Date started 06/09/2003, 19__
Date completed 06/10/2003, 19__

7. WELL TEST DATA

TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 410 Feet Depth Cased 410 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
Inches	Feet	Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
14		.188	100	300
10"		10 gage	290'	410'?

Perforations:
Type perforation torched, slotted and Mills Knife
Size perforation
From feet to feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 400'
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout
Gravel Packed: ☐ Yes ☒ No
From feet to feet

9. WATER LEVEL
Static water level 16' feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Carson Pump
Contractor
Address P.O. Box 20159
Contractor
Carson City, NV. 89721
Nevada contractor's license number issued by the State Contractor's Board 39920
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1482
Signed Daniel Trompe
By driller performing actual drilling on-site or contractor
Date 06/20/2003

USE ADDITIONAL SHEETS IF NECESSARY