REPORT NO. A03.087

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

LOG NO. 91841
PERMIT NO.
BASIN 083

NOTICE OF INTENT NO 51441

1. OWNER Cotton Clark
MAILING ADDRESS 212 Blew De Clair Sparks, NV 89434

ADDRESS OF WELL 2045 Flint Rd.
Virginia City Highlands, NV 89521

2. WELL LOCATION SW 1/4 SW 1/4 SEC. 32 T 18 R 21 E Storey COUNTY

PERMIT NO PARCEL NO 03-092-87 SUBDIVISION NAME

3. TYPE OF WORK
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Plug [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [ ] Mud

6. LITHOLOGIC LOG

MATERIAL	STRATA	FROM	TO	THICKNESS
Dirt Yellow Rock & Clay		0	45	45
Yellow Rock & Red Volcanic Rock		45	130	85
Multi Color Volcanic Rock		130	170	40
Gray Blue Volcanic Rock		170	195	25
Blue Green Rock		195	330	135
Blue Green Granite		330	404	74

8. WELL CONSTRUCTION
Depth Drilled 404 Depth Cased 404

HOLE DIAMETER (BIT SIZE
10 Inches 0 Feet 50 Feet
8 1/2 Inches 50 Feet 404 Feet
Inches Feet Feet

CASING SCHEDULE

Size OD	Weight/Ft	Wall Thickness	From	To
6 5/8	12.92	.188	+2	404

PERFORATIONS:
Type Perforation Factory Size Perforation 3/32 X 3
From 364 Feet to 404 Feet
From Feet to Feet
From Feet to Feet

SURFACE SEAL: [X] Yes [ ] No
Seal Depth 50
PLACEMENT METHOD [ ] Pumped [X] Poured
SEAL TYPE: [ ] Neat Cement [ ] Cement Grout [X] Concrete Grout [ ] Bentonite

GRAVEL PACKED: [X] Yes [ ] No
From 50 Feet to 404 Feet

9. WATER LEVEL
Static Water Level 288 Feet Below Land Surface
Artesian Flow GPM PSI
Water Temperature cool F Quality clear

Notes :

Date Started 9/3/03 Date Completed 9/8/03

7. WELL TEST DATA

TEST METHOD [ ] Bailer [ ] Pump [X] Air Develop

	GPM	DRAWDOWN	TIME (HRS)
	20+		1hr.

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Aqua Drilling & Well Service, Inc.
Address 675 Edison Way
Reno, NV 89502

NV. CONTRACTOR'S LIC. NO 15291 DRILLER'S LIC. NO ON SITE 2189

Signed Roger M Thull
By driller performing actual drilling on site or contractor

Dated September 8, 2003