KL-#1

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 91847
Permit No.
Basin 87

NOTICE OF INTENT NO. 46092

1. OWNER Public Works / City of Reno
MAILING ADDRESS P.O. Box 1900
Reno, Nv. 89505

ADDRESS AT WELL LOCATION West of Virginia St. in Parking Area South Side of 3rd St.
Reno, Nevada 89505

2. LOCATION SW ¼ NE ¼ Sec. 11 T. 19 N/S R. 19 E. Washoe County
PERMIT NO. DEW-30 (Issued by Water Resources) | 011-370-43 (Parcel No.) | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other Sonic

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Asphalt & Fill		0'	1'	1'
Cobbles - Grey - Dry		1'	3'	2'
Silty Clay - Brown - Dry		3'	5'	2'
Silt - Greyish Brown - Dry		5'	10'	5'
Silty SAND - Grey - Dry		10'	19'	9'
Gravely SAND - Grey - Dry		19'	24'	5'
Cobbles (Gravel) - Greyish White Dry		24'	35'	11'

Date started 1-13-, 2004
Date completed 1-13-, 2004

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 35' Feet Depth Cased 35' Feet

HOLE DIAMETER (BIT SIZE)

	From	To
6" Inches	0' Feet	35' Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2"	Sch. 40	P.V.C.	0'	25'

Perforations:
Type perforation Factory Cut
Size perforation 0.020"
From 25' feet to 35' feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 23'
Placement Method: ☐ Pumped ☒ Poured
Gravel Packed: ☒ Yes ☐ No
From 35' feet to 23' feet

Seal Type:
☐ Neat Cement
☐ Cement Grout
☐ Concrete Grout
Bentonite Chips
3' Concrete

9. WATER LEVEL
Static water level NONE At time of install feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Phillip Cramer / Boart Longyear (Contractor)
Address P.O. Box 1000 Dayton, Nv. 89403 (Contractor)
32 Stokes Dr. Dayton, Nv. 89403
Nevada contractor's license number issued by the State Contractor's Board 0040157
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-2148
Signed Phillip E. Cramer
By driller performing actual drilling on site or contractor
Date 1-15-04

(Rev. 12-01) USE ADDITIONAL SHEETS IF NECESSARY (O)-627