WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 41853
Permit No. ~~19396 - 22928~~ 79138T
Basin 139

NOTICE OF INTENT NO. 48640

1. OWNER Star Creek Ranch - Robert Pruitt
MAILING ADDRESS 2377 Shield Ave.
La Crescenta, CA 91214

ADDRESS AT WELL LOCATION 10900 Hwy 400, Imlay
Nevada

2. LOCATION NE 1/4 NW 1/4 Sec. 28 T 31 N/S R 35 E Humboldt County
PERMIT NO. ~~79138 19396~~ Issued by Water Resources | Parcel No. | Subdivision Name

3. WORK PERFORMED
[X] New Well ~~[X] Replace~~ [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [X] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [X] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
surface soil		0	5	
sand & gravel w/cobbles		5	108	103
coarse sand & gravel		108	130	22
sand & gravel w/cobbles		130	151	21
hard cemented gravel		151	163	12
sand & gravel w/cobbles		163	385	222
sandy clay		385	411	26

~~Replacement of log 6349~~

RECEIVED
03 JUL 28 AM 11:17
STATE ENGINEERS OFFICE

Date started 7/15/03, 19__
Date completed 7/23/03, 19__

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [X] Pump [ ] Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
P/L169.27	2200	20.87	15 hr

8. WELL CONSTRUCTION
Depth Drilled 411 Feet Depth Cased 400 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
36	Inches	0	Feet	50	Feet
24	Inches	50	Feet	411	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
16		.250	+1	120
30		.250	+1	50

Perforations:
Type perforation Double row mill slot
Size perforation .90 x 3
From 120 feet to 400 feet
From ___ feet to ___ feet
From ___ feet to ___ feet
From ___ feet to ___ feet
From ___ feet to ___ feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50
Placement Method: [X] Pumped [ ] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 3 feet to 411 feet

9. WATER LEVEL
Static water level 148.5 feet below land surface
Artesian flow ___ G.P.M. ___ P.S.I.
Water temperature cool °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Humboldt Drilling & Pump Co., Inc. (Contractor)
Address 4675 W. Winnemucca Blvd (Contractor)
Winnemucca, Nevada 89445

Nevada contractor's license number issued by the State Contractor's Board 015234

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1713

Signed [signature] (By driller performing actual drilling on-site or contractor)
Date 7/26/03