WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 92160
Permit No.
Basin 66

NOTICE OF INTENT NO. 51835

1. OWNER Newmont mining Corp
MAILING ADDRESS P.O. Box 388
Valmy NV, 89438
ADDRESS AT WELL LOCATION Twin Creeks mine

2. LOCATION NE ¼ SW ¼ Sec. 30 T 39 N/S R 43 E Humbolt County
PERMIT NO. Issued by Water Resources | Parcel No. | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
M/O 30-21 A				
Alluvium 0-710				
Bed rock 710-740 TD				
Set 4½ Casing to Bottom				
Set 1½ to Bottom				
Place gravel in hole with trimmy from Bottom to 340' - 6 Yrd 3				
Place 800 gal Abandonite in hole with trimmy from 340' to 60'				
Pour in 5 Bags Kwik Plug Casing Seal				
Set monument and Cement top 50'				
Develope well				

RECEIVED 04 FEB -9 AM 9:55 STATE ENGINEERS OFFICE

Date started 01/13/2004, 19
Date completed 01/29/2004, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
>30		

8. WELL CONSTRUCTION
Depth Drilled 740 Feet Depth Cased 740 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
14¾ Inches	0 Feet	40 Feet
10 Inches	40 Feet	740 Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4½	PVC	Sc 80	0	740
1½	PVC	Sc 80	0	740

Perforations:
Type perforation Slot
Size perforation .020
From 4½) 440 feet to 720 feet
From 1½) 480 feet to 720 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50'
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 340 feet to 740 feet

9. WATER LEVEL
Static water level 232 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling (Contractor)
Address P.O. Box 2748 (Contractor)
Elko NV, 89803
Nevada contractor's license number issued by the State Contractor's Board 0030823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-2089
Signed [signature]
By driller performing actual drilling on site or contractor
Date 01/29/04