WHITE–DIVISION OF WATER RESOURCES
CANARY–CLIENT'S COPY
PINK–WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 92221
Permit No.
Basin 137B

NOTICE OF INTENT NO. 51150

1. OWNER Round Mt Gold Corp
MAILING ADDRESS P.O Box 480 Round Mountain Nevada 89045
ADDRESS AT WELL LOCATION Gold Hill
2. LOCATION SW ¼ NE ¼ Sec. 32 T 11 ☒S R 44 E Nye County
PERMIT NO. (Issued by Water Resources) Parcel No. Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic Dual ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Alluvium Gravel Sand		0	500	500
Clay		500	825	325
Hard Rock with fractures		825	960	135
1" sch 40 PVC	Blank	+3	920	920
1" sch 40 PVC	Blank	940	960	20
1" sch 40 PVC	Screen .020 slot	920	940	20
146 #50 Bags #8 Sand		900	960	60
40 #94 Bags Cement		770	900	130
30 #50 Bags Attapulgite		60	770	710
6 #100 Bags #60 Sand		50	60	10
20 #94 Bags Cement		+3	50	53

Date started 10-29, 2003
Date completed 11-17, 2003

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
Approx 100	N/A	12

8. WELL CONSTRUCTION
Depth Drilled 960 Feet Depth Cased 950 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
16 Inches		0 Feet	60 Feet
8 3/4 Inches		60 Feet	960 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
10"		3/16 wall	+3	60
4"	sch 80 PVC		+3	920
4"	sch 80 PVC		940	960

Perforations:
Type perforation Horiz factory
Size perforation .020
From 920 feet to 940 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 900 feet to 960 feet

9. WATER LEVEL
Static water level 9' 6" feet below land surface
Artesian flow None G.P.M. P.S.I.
Water temperature 34.6 °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Co Inc (Contractor)
Address P.O. Box 2748 Elko, Nevada 89803 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board 0030823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1879
Signed [signature] (By driller performing actual drilling on site or contractor)
Date 11-17-03

USE ADDITIONAL SHEETS IF NECESSARY

(Rev. 12-01) (O)-627