LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	0	180	180'	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

50' Drawdown @ 10 G.P.M.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed [signature]
Well Driller

By

License No. 245

Dated May 19, 1961

1961 MAY 22 AM 9 52
STATE ENGINEER
OFFICE

(Not to be filled in by Driller)

1962 DEC 3 PM 4 06
STATE ENGINEER
OFFICE

(1)

Log No. 92329 ~~5890d~~
Rec. May 22 19 61
Well No.
Permit No.
Do not fill in

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner: Ottie H. Andrews Driller: Reno Pump & Supply

Address: P.O. Box 55 Black Springs, Nev. Address: 7468 So. Virginia - Reno Lic. No. 295

Location of well: SE 1/4 NW 1/4 Sec. 36, T. 20 N/S, R. 19 E, in Washoe County

or

Water will be used for: Domestic Total depth of well: Deepen 6" Well to 190'

Size of drilled hole: 6" Weight of casing per linear foot:

Thickness of casing: 12 Ga. Temp. of water: Cold

Diameter and length of casing: 6" x 180'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface:

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: 7/19/60 Date of completion of well: 7/25/60

Type of well rig: Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
98'	190'	92'	Clay with thin streaks of w/b material

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 88 to 180 ft.

Other aquifers:

First water at 88 feet.

Casing perforated
from 88 to 180 ft.

Size of perforations
Mills Knife Perforations

919