WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 93164
Permit No.
Basin 105

NOTICE OF INTENT NO. 51677

1. OWNER James Adams
MAILING ADDRESS 2548 Fremont St.
Minden, NV 89423

ADDRESS AT WELL LOCATION 2548 Fremont St.

2. LOCATION NW 1/4 NW 1/4 Sec. 2 T 13N N/S R 20E E Douglas County
PERMIT NO. (Issued by Water Resources) 1320-02-001-037 (Parcel No.) Subdivision Name

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☒ Other mud

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
On this date we abandoned a 8" X 150' well deepened from 150' to 200' with a 6" liner from 150' to 200'. We perforated with a Mills Kinfe at 4 around and at one foot intervals.We perforated from 150' to 50'. There was a sanitary seal.We then pumped 2.75 Cu. Yards of neat cement mixed 5.2 gallons of water per sack. We pumped, using tremie pipe, from the bottom to 70'. We then topped it off with sand grout to the top. We then cut off the top 2' of the well.				

RECEIVED 04 APR 22 AM 11:08 STATE ENGINEER'S OFFICE

Date started 4/19/2004 , 19__
Date completed 4/19/2004 , 19__

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 200 Feet Depth Cased 200 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
Inches	Feet	Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8 5/8	18.6	.188	-2	150
6 5/8	12.92	.188	150	200

Perforations:
Type perforation Mills Knife
Size perforation Puncture
From 50 feet to 150 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50
Placement Method: ☐ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☐ Concrete Grout
Gravel Packed: ☒ Yes ☐ No
From 50 feet to 150 feet

9. WATER LEVEL
Static water level 126 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature Cool °F Quality Not tested

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Bruce MacKay Pump & Well Service, Inc. (Contractor)
Address 1600 Mt. Rose Hwy (Contractor)
Reno, NV 89511
Nevada contractor's license number issued by the State Contractor's Board 23096
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2159
Signed R. Bruce MacKay (By driller performing actual drilling on-site or contractor)
Date 4/19/1904

USE ADDITIONAL SHEETS IF NECESSARY