


OFFICE USE ONLY  
 Log No. 93179  
 Permit No. \_\_\_\_\_  
 Basin 66  
  
 NOTICE OF INTENT NO. 51846

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

1. OWNER Newmont Gold Corp. ADDRESS AT WELL LOCATION Twin Creeks Mine  
 MAILING ADDRESS P.O. Box 388  
Valmy, NV. 89438  
 2. LOCATION NW 1/4 SE 1/4 Sec 30 T. 39 N R 43 E Humboldt County  
 PERMIT NO. \_\_\_\_\_ Issued by Water Resources Parcel No. \_\_\_\_\_ Subdivision Name \_\_\_\_\_

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other \_\_\_\_\_  
 4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
 5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other \_\_\_\_\_

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
<u>Brown Clay &amp; Gravel</u>		<u>0</u>	<u>7.25</u>	<u>7.25</u>
<u>Red Clay &amp; Gravel</u>		<u>7.25</u>	<u>7.25</u>	<u>20</u>
<u>Materials Used:</u>				
<u>7 Cu. Sq. Yds. Gravel</u>				
<u>148 Kwik Plug Med. 50lb. ea</u>				
<u>17 Cement 94lb.</u>				
<u>6 W-60 50lb.</u>				

8. WELL CONSTRUCTION  
 Depth Drilled 725 Feet Depth Cased 720 Feet  
 HOLE DIAMETER (BIT SIZE)  
 From To  
14 Inches 0 Feet 40 Feet  
10 Inches 40 Feet 725 Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>1 1/2</u> Nominal		<u>5-80</u>	<u>0</u>	<u>720</u>
<u>4"</u> Nominal		<u>5-80</u>	<u>0</u>	<u>720</u>

Perforations:  
 Type perforation Slot  
 Size perforation 1.020  
 From (1 1/2") 480 feet to 680 feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From (4") 320 feet to 680 feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  Neat Cement  
 Depth of Seal 52 ft.  Cement Grout  
 Placement Method:  Pumped  Boured  Concrete Grout  
 Gravel Packed:  Yes  No  
 From 383 feet to 725 feet

9. WATER LEVEL  
 Static water level 210 feet below land surface  
 Artesian flow N/A G.P.M. \_\_\_\_\_ P.S.I. \_\_\_\_\_  
 Water temperature \_\_\_\_\_ °F Quality \_\_\_\_\_

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name EKlund Drilling Contractor  
 Address P.O. Box 2748 Contractor  
ETKO, NV. 89803  
 Nevada contractor's license number issued by the State Contractor's Board 0030823  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-2260  
 Signed [Signature]  
 By driller performing actual drilling on site or contractor  
 Date 4-15-04

Date started April 05 2004  
 Date completed April 15 2004

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input checked="" type="checkbox"/> Air Lift	<u>T.D. 75</u>		