WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 93519
Permit No.
Basin 212

NOTICE OF INTENT NO. 26392

1. OWNER Kinder Morgan Energy Partners
MAILING ADDRESS 370 Van Gordon St. Lakewood Co. 80228-8304
ADDRESS AT WELL LOCATION 575 Kitty Hawk Way. McCarren International Airport, Las Vegas, Nev.
2. LOCATION NW ¼ SW ¼ Sec. 27 T 21 N R 61 (E) Clark County
PERMIT NO. Issued by Water Resources
Parcel No. 1622730 1001
Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other Auger

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sand yellowish				
Fine gravel		0	8	8
light gray Clay				
Caliche Coarse				
Sand.		8	15	7
STiFF Clay				
Caliche		15	20	5
Sandy silt				
light Clay med.				
Sand.		20	25	5
Clay light gray				
Wet Trace of				
Coarse Sand	26	25	30	5
Sandy silt				
light gray wet				
Fine to Med Sand.		30	35	5
Sandy Clay pink				
very stiff wet				
Coarse grain Sand		35	47	12
saturated				

DCNR/DWR
RECEIVED
JUN 21 2004
LAS VEGAS OFFICE

Date started June 8, 2004
Date completed June 8, 2004

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
N/A		
Client will develop at a later date		

8. WELL CONSTRUCTION
Depth Drilled 47 Feet Depth Cased 47 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
9 Inches	0 Feet	47 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4.5	2.006	.237	1	16.5

Perforations:
Type perforation Machine slot
Size perforation .010
From 16.5 feet to 46.5 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 11.5 To 1' below grade
Placement Method: ☐ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout
11.5 To 14.5 Bent. pellets
Gravel Packed: ☒ Yes ☐ No
From 14.5 feet to 47 feet

9. WATER LEVEL
Static water level 26 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature N/A °F Quality N/A

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Layne Christenson Co. (Contractor)
Address 2030 F. Riggs Rd. Chandler Az. 85249 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board 0019101
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-2215
Signed Ruby L. Miller (By driller performing actual drilling on site or contractor)
Date 6-11-04

USE ADDITIONAL SHEETS IF NECESSARY

(Rev. 12-01) (O)-627