

OFFICE USE ONLY
 Log No. 93380
 Permit No. _____
 Basin. 66

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT
 Please complete this form in its entirety in
 accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 52063

1. OWNER Newmont Mining ADDRESS AT WELL LOCATION _____
 MAILING ADDRESS P.O. Box 388 Twin Creeks Mine
Valmy, NV 89438
 2. LOCATION NW 1/4 SW 1/4 Sec. 30 T. 39 NS R. 43 E Humboldt County _____
 PERMIT NO. _____ Issued by Water Resources Parcel No. _____ Subdivision Name _____

3. WORK PERFORMED New Well Replace Recondition
 Deepen Abandon Other _____
 4. PROPOSED USE Domestic Dual Irrigation Test
 Municipal/Industrial Monitor Stock
 5. WELL TYPE Cable Rotary RVC
 Air Other _____

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
<u>Alluvium - Gravel sands + Clay</u>		<u>0</u>	<u>760</u>	<u>760</u>
<u>Red waxy Clay</u>		<u>760</u>	<u>860</u>	<u>100</u>
<u>Hard Rock</u>		<u>860</u>	<u>940</u>	<u>80</u>
<u>Cement Hole Back</u>		<u>940</u>	<u>580</u>	<u>360</u>
<u>120 - 94# Bags Cement</u>				
<u>1 1/2" sch 80 PVC Blank</u>		<u>+2</u>	<u>200</u>	<u>200</u>
<u>1 1/2" sch 80 PVC Screen</u>		<u>200</u>	<u>500</u>	<u>300</u>
<u>1 1/2" sch 80 PVC Blank</u>		<u>500</u>	<u>580</u>	<u>80</u>
<u>7 - 2500# Bags 1/4 Gravel</u>		<u>180</u>	<u>580</u>	<u>400</u>
<u>70 - 50# Bags Medium Quik Plug</u>		<u>50</u>	<u>180</u>	<u>130</u>
<u>17 - 94# Bags Cement</u>		<u>+2</u>	<u>50</u>	<u>52</u>

8. WELL CONSTRUCTION
 Depth Drilled 942 Feet Depth Cased 580 Feet
 HOLE DIAMETER (BIT SIZE)
 From _____ To _____
1 1/4 Inches 0 Feet 40 Feet
10 Inches 40 Feet 940 Feet
 _____ Inches _____ Feet _____ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>10 3/4</u>		<u>3/16</u>	<u>42</u>	<u>40</u>
<u>4 1/2</u>	<u>11.3</u>	<u>3/16</u>	<u>72</u>	<u>200</u>
<u>4 1/2</u>	<u>11.3</u>	<u>3/16</u>	<u>500</u>	<u>580</u>

Perforations:
 Type perforation Vertical mill slot
 Size perforation 3/16
 From 200 feet to 500 feet
 From _____ feet to _____ feet
 Surface Seal: Yes No Seal Type: Neat Cement
 Depth of Seal 50 Cement Grout
 Placement Method: Pumped Concrete Grout
 Poured
 Gravel Packed: Yes No
 From 180 feet to 580 feet

9. WATER LEVEL
 Static water level 167 feet below land surface
 Artesian flow _____ G.P.M. _____ P.S.I.
 Water temperature _____ °F Quality _____

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name Eklund Drilling Co Inc Contractor
 Address P.O. Box 2748 Contractor
Elko, NV 89803
 Nevada contractor's license number 0030823 issued by the State Contractor's Board
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1879
 Signed [Signature] By driller performing actual drilling on site or contractor
 Date 5-19-04

Date started April 20, 2004
 Date completed May 17, 2004

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input checked="" type="checkbox"/> Air Lift	<u>30</u>	<u>N/A</u>	<u>12</u>

RECEIVED
 JUN 14 AM 10:55
 STATE ENGINEERS OFFICE