WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 93929
Permit No.
Basin 65

NOTICE OF INTENT NO. 52066

1. OWNER Newmont mining Corp
MAILING ADDRESS PO Box 388
Valmy, NV 89438

ADDRESS AT WELL LOCATION
Lone Tree mine well # 8
Stonehouse exit I-80 Nevada

2. LOCATION SW ¼ SW ¼ Sec. 1 T. 34 N/S R. 42 E. Humbolt County
PERMIT NO. 57103 (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☒ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
9-50 lb Bags of Super plug per 400 gal Tub				
Abandone well				
from Bottom to				
top 80' with				
Trimmy Pump				
455 Bags Super				
plug Abandonk in				
hole 150% of Volume				
get Fluid with in				
80' of Surface Pour				
3 Super Sacks of 3/8				
hole plug in to Bring				
level up to 20' of Surface				
pour in 230 gal Cement				
25-94lb Sacks Cement - (neat)				
Abandonment materials				
455 Sacks Super plug (50# ea)				
3 Super Sacks 3/8 Hole plug (2500# ea)				
25 Sacks Neat Cement (94# ea)				

RECEIVED MAY 24 AM 10 ENGINEERS FILE

Date started 5/11/2004, 19
Date completed 5/12/2004, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 601 Feet Depth Cased 601 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From (Feet)	To (Feet)
24	0	601

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
16	46	.281	0	601

Perforations:
Type perforation Slot and Screen
Size perforation
From 58 feet to 591 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 20
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout
Gravel Packed: ☐ Yes ☐ No
From feet to feet

9. WATER LEVEL
Static water level None feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling (Contractor)
Address PO Box 2748 (Contractor)
Elko, NV 89803
Nevada contractor's license number issued by the State Contractor's Board 0030823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1776
Signed [signature] (By driller performing actual drilling on site or contractor)
Date 5/12/04

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627