

STATE OF NEVADA
 DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
 Log No. 93979
 Permit No. 55142
 Basin 001

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

Please complete this form in its entirety in
 accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 51974

1. OWNER Barrick Goldstrike Mines BW-25 ADDRESS AT WELL LOCATION Barrick Goldstrike
 MAILING ADDRESS P.O. Box 29 minesite, north of Carlin, NV.
Elko, NV 89803

2. LOCATION SE 1/4 SW 1/4 Sec. 24 T 36N N/S R 49 E Eureka County
 PERMIT NO. 55142 Parcel No. N/A Subdivision Name N/A
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other

4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
The current mine plan has this well being mined off to 640' depth. Prior to abandoning, well was perforated from 640' - 690', 12 passes with the perforator.				
Abandoned by pumping abantonite via tremie from T.D. to 1790', where it would rise no other.				
Built hole plug bridge and a cement bridge, then poured hole plug while pumping abantonite.		1820	1810	-10
Pumped neat cement		1810	1803	-7
Pumped abantonite			692	-1111
Pumped neat cement		692	592	-100
Pumped neat cement		592	260	-332
Clean fill		260	250	-10
Neat cement		250	20	-230
		20	0	-20
Quantities Used:				
Cement: 375 cu. ft.				
Continued on next page				

Date started 8/6/2004 , 19
 Date completed 8/14/2004 , 19

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			

8. WELL CONSTRUCTION

Depth Drilled 2044 Feet Depth Cased 2030 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From	Feet	To	Feet
<u>48</u>		<u>0</u>	<u>78</u>	
<u>31</u>		<u>78</u>	<u>2044</u>	

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>40</u>	<u>158.70</u>	<u>0.375</u>	<u>0</u>	<u>78</u>
<u>24</u>	<u>94.69</u>	<u>0.375</u>	<u>0</u>	<u>2030</u>

Perforations:

Type perforation Louwer
 Size perforation 0.125"

From	Feet to	Feet
<u>310</u>	<u>350</u>	
<u>510</u>	<u>550</u>	
<u>870</u>	<u>910</u>	
<u>1230</u>	<u>1270</u>	
<u>1590</u>	<u>1990</u>	

Surface Seal: Yes No Seal Type:
 Depth of Seal 100' Neat Cement
 Placement Method: Pumped Cement Grout
 Poured Concrete Grout

Gravel Packed: Yes No
 From 100 feet to 2044 feet

9. WATER LEVEL

Static water level 1790.7 feet below land surface
 Artesian flow N/A G.P.M. _____ P.S.I. _____
 Water temperature 140 °F Quality Fair

10. DRILLER'S CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Lang Exploratory Drilling Contractor
 Address P.O. Box 5279 Contractor
Elko, NV 89802-5279
 Nevada contractor's license number issued by the State Contractor's Board 0021976
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1410

Signed John Viergutz
 By driller performing actual drilling on-site or contractor
 Date 8/17/04

BSTA

