WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 95391
Permit No.
Basin 207

NOTICE OF INTENT NO. 432.00

1. OWNER Brent Gardner
MAILING ADDRESS Po Box 220 Lund NV 89317
ADDRESS AT WELL LOCATION 500 N 100W Lot 3 Block 19 Lund town plot

2. LOCATION NW ¼ SW ¼ Sec. 28 T. 12 N/S R. 62 E. White Pine County
PERMIT NO. 66603 (Issued by Water Resources) 013-111-08 (Parcel No.) none (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☒ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☒ Cable ☐ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
clay gravel conglomerate		1	4	
Sandy Clay		4	15	
clay gravel		15	16	
Sandy Clay		16	37	
gravel	water	37	38	1
Clay		38	51	
Sand gravel cobbles	water	51	56	5
Sandy clay		56	61	
gravel	water	61	62	1
Sandy clay		62	76	
gravel	water	76	77	1
Sandy Clay		77	82	
gravel	water	82	83	1
Sandy Clay		83	89	
gravel strata at	water	89	90	1
with sandy clay		99	100	1
in between		114	115	1
		122	123	1
		134	136	2
		141	142	1
		150	151	1
	water	174	175	1
Sandy Clay		175	180	

RECEIVED AUG 15 2004 ENGINEERS OFFICE

Date started January 10 2004
Date completed July 4 2004

7. WELL TEST DATA
TEST METHOD: ☒ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
110	1	1

8. WELL CONSTRUCTION
Depth Drilled 180 Feet Depth Cased 180 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
22 Inches		0 Feet	51 Feet
20 Inches		51 Feet	160 Feet
16 Inches		160 Feet	180 Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
16		250	-1	180

Perforations:
Type perforation mill
Size perforation 5/32 x 2.5" x 32 rows
From feet to feet
From 50 feet to 180 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50
Placement Method: ☒ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 140 feet

9. WATER LEVEL
Static water level 37 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature cold °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Maynard well Drilling (Contractor) Orson Maynard
Address Po Box 64 Lund NV 89317 (Contractor)

Nevada contractor's license number issued by the State Contractor's Board 47224
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1556
Signed Orson Maynard (By driller performing actual drilling on site or contractor)
Date Aug 1-04

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627