WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT
Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 95487
Permit No.
Basin 103

NOTICE OF INTENT NO. 49548

1. OWNER Dayton Land Developement
MAILING ADDRESS 451 Lakeshore Drive
Incline Village, NV 89451

ADDRESS AT WELL LOCATION Santa Maria Ranch, Hwy 50, Dayton, NV.

2. LOCATION NE 1/4 SE 1/4 Sec. 27 T 16N N/S R 21E E Lyon County
PERMIT NO. n/a (Issued by Water Resources) n/a (Parcel No.) (Subdivision Name)

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Casing was 6". Measured static water level at 32.1'. Measured depth of well at 286'. Tried to bail well but could not retreive any debris. Spoke with Tom Gallagher about abandonment since we could not find log on well. We perforated from 50' to surface with Mills Knife, cutting 4 rows per foot. We then installed 283' of 2" tremme pipe and pumped in approximately 3 yards of neat cement. Well volume shaould have required 2 yards.				

RECEIVED 04 NOV 17 AM 11:59 STATE ENGINEER'S OFFICE

Date started 11/04/2004, 19__
Date completed 11/06/2004, 19__

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled ____ Feet Depth Cased ____ Feet

HOLE DIAMETER (BIT SIZE)

	From	To
Inches	Feet	Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6"		.188"	+2	286'

Perforations:
Type perforation Mills Knife
Size perforation
From 50' feet to surface feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 286'
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☐ Yes ☒ No
From feet to feet

9. WATER LEVEL
Static water level 32.1' feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Carson Pump (Contractor)
Address P.O. Box 20159 (Contractor)
Carson City, NV. 89721
Nevada contractor's license number issued by the State Contractor's Board 39920
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1482
Signed Dan Granger (By driller performing actual drilling on-site or contractor)
Date 11/15/2004

USE ADDITIONAL SHEETS IF NECESSARY