

MW-9

WHITE-DIVISION OF WATER RESOURCES  
CANARY-CLIENT'S COPY  
PINK-WELL DRILLER'S COPY

STATE OF NEVADA  
DIVISION OF WATER RESOURCES

OFFICE USE ONLY  
Log No. 95497  
Permit No. \_\_\_\_\_  
Basin φ42

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

WELL DRILLER'S REPORT  
Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 54930

1. OWNER Fearless Ferris Corporation ADDRESS AT WELL LOCATION 1010 Sixth Street Wells Nevada  
MAILING ADDRESS RD. Box 7627 Boise Idaho 83707  
2. LOCATION N.W. 1/4 S.E. 1/4 Sec. 10 T. 37N R. 62 E. Elko County  
PERMIT NO. M 70-1345 002-760-001 Subdivision Name \_\_\_\_\_  
Issued by Water Resources Parcel No. \_\_\_\_\_

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other \_\_\_\_\_  
4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other Direct Push

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
<u>Engineered Backfill</u>		<u>0</u>	<u>9.8</u>	
<u>Brown-Black, some asphalt</u>				
<u>Clayey Sand Gray</u>		<u>9.8</u>	<u>14.0</u>	
<u>Gravelly Sand</u>		<u>14.0</u>	<u>14.6</u>	
<u>Clayey Sand</u>		<u>14.6</u>	<u>15</u>	
<u>Grays Green</u>				

GPS 11T-067-1260  
UTM-4552113

\* Water was still rising slowly and may take 1-2 days to reach true static

8. WELL CONSTRUCTION  
Depth Drilled \_\_\_\_\_ Feet Depth Cased \_\_\_\_\_ Feet  
HOLE DIAMETER (BIT SIZE)  
From \_\_\_\_\_ To \_\_\_\_\_  
10 Inches 9 Feet 1 Feet  
3.5 Inches 9 Feet 15 Feet  
\_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>1.875</u>		<u>Sch 40 PVC</u>	<u>.25</u>	<u>5</u>

Perforations:  
Type perforation Factory Slotted (PVC)  
Size perforation .020  
From 5 feet to 15 feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type: \_\_\_\_\_  
Depth of Seal 3 ft Bentonite-3  Neat Cement  
Placement Method:  Pumped  Poured 0-1  Concrete Grout  
Gravel Packed:  Yes  No Flush Mount  
From 3 (10-20) feet to 15 feet

9. WATER LEVEL  
Static water level 13.97 \* feet below land surface  
Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
Water temperature \_\_\_\_\_ °F Quality \_\_\_\_\_

Date started Dec. 14, 2004  
Date completed Dec. 14, 2004

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailor <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision and the report is true to the best of my knowledge.  
Name Layne Christensen Company Contractor  
Address 4490 West 1707 South Salt Lake City Utah 84104 Contractor  
Nevada contractor's license number issued by the State Contractor's Board 0019101  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1970  
Signed Wilburn L. Franklin  
By driller performing actual drilling on site or contractor  
Date Dec. 14, 2004