

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

45537  
7060

Log No. \_\_\_\_\_  
 Rec. \_\_\_\_\_ 174 1950  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_

*Do not fill in*

Owner N. S. Land Management Driller Mel Meyer

Address P. O. BOX 539 Susanville, Calif Address 120 Hoana Lane Reno, Lic. No. 3

Location of well: NW 1/4 ne 1/4 Sec. 22, T. 23N/S, R. 20E, in Washoe County  
 or Doyers

Water will be used for Stock Total depth of well 100'

Size of drilled hole 8" Weight of casing per linear foot 20#

Thickness of casing 5/16 Temp. of water Cold

Diameter and length of casing 6" id X 100'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 60'

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well 12-1-50 Date of completion of well 12-4-50

Type of well rig Cable Tool

LOG OF FORMATIONS				Water-bearing Formation, Casing Perforations, Etc.
From feet	To feet	Thickness feet	Type of material	
0	60	60	Red Clay Sand	
60	100	40	Yellow Clay Gravel	
				Chief aquifer (water-bearing formation)
				from <u>85'</u> to <u>100' 1/2</u> ft.
				Other aquifers _____
				First water at <u>85</u> feet.
				Casing perforated
				from <u>70</u> to <u>100</u> ft.
				Size of perforations
				<u>1/2 X 1/2"</u>



