

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK



Log No. 95622  
 Permit No. 096  
 Basin 096

NOTICE OF INTENT NO. 54018

1. OWNER DOMINIS BROWN, STELLOEL PRODUCTS US ADDRESS AT WELL LOCATION 212 TRAIL ELKS POINT RA, ZEPHYR COVE NV (TREN WEST RESORT)  
 MAILING ADDRESS 20945 SOUTH WILMINGTON AVE CARSON, CA  
 2. LOCATION NE 1/4 SE 1/4 Sec. 15 T. 13 S. R. 18 E DOUGLAS County  
 PERMIT NO. 1318-15-802-D10  
 Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other  
 4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
 5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other POTTSVILLE

6. LITHOLOGIC LOG

| Material                       | Water Strata | From | To   | Thick-ness |
|--------------------------------|--------------|------|------|------------|
| FINE TO COARSE SAND (SW)       |              | 0    | 4    | 4          |
| CLAYEY SAND (SL)               |              | 4    | 6    | 2          |
| FINE SILTY SAND (SM)           |              | 6    | 9    | 3          |
| FINE TO COARSE SAND (SW)       |              | 9    | 14   | 5          |
| FINE TO COARSE SILTY SAND (SM) |              | 14   | 19   | 5          |
| FINE CLAYEY SAND (SL)          |              | 19   | 21   | 2          |
| FINE SAND (SP)                 | 14-30        | 21   | 23   | 2          |
| FINE CLAYEY SAND (SL)          |              | 23   | 26.5 | 3.5        |
| FINE SAND W/ GRAVEL (SLO)      |              | 26.5 | 30.5 | 4          |
| GRANITE BEDROCK                |              | 30.5 | 33   | 2.5        |

8. WELL CONSTRUCTION  
 Depth Drilled 33 Feet Depth Cased 33 Feet  
 HOLE DIAMETER (BIT SIZE)  
 From 0 To 33  
8 Inches 0 Feet 33 Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|--------------------|---------------------|-------------------------|-------------|-----------|
| <u>2.25</u>        | <u>Sch 40</u>       | <u>0.25</u>             | <u>0</u>    | <u>33</u> |

Perforations:  
 Type perforation SLOTTED  
 Size perforation 0.020"  
 From 18 feet to 33 feet  
 From 20 feet to 44 feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  
 Depth of Seal 16  Neat Cement  
 Placement Method:  Pumped  Cement Grout  
 Poured  Concrete Grout  
 Gravel Packed:  Yes  No  
 From 16 feet to 33 feet

9. WATER LEVEL  
 Static water level 18 feet below land surface  
 Artesian flow NO G.P.M. \_\_\_\_\_ P.S.I. \_\_\_\_\_  
 Water temperature \_\_\_\_\_ °F Quality \_\_\_\_\_

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name Robert Solois (BOART LONGYEAR CO) Contractor

Address 7773 W, SELDON LN PEORIA, AZ 85345 Contractor  
 Nevada contractor's license number issued by the State Contractor's Board 0010157  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller m-2270  
 Signed Robert Solois  
 By driller performing actual drilling on site or contractor  
 Date 12-27-04

Date started DECEMBER 15, 2004  
 Date completed DECEMBER 16, 2004

7. WELL TEST DATA

| TEST METHOD:  | G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|--------|-------------------------------|--------------|
| <input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift |        |                               |              |
|   |        |                               |              |
|   |        |                               |              |
|   |        |                               |              |

05 MAR - 1 AM 10:05  
 STATE ENGINEERS OFFICE