WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 95638
Permit No.
Basin 110A

NOTICE OF INTENT NO. 47966

1. OWNER US Geological Survey
MAILING ADDRESS 333 W Nye Ln
Carson City Nv 89706

ADDRESS AT WELL LOCATION Walker River Indian Reservation Weber Gage

2. LOCATION NW ~~SW~~ SE ~~NW~~ ¼ Sec. 2 T. 14 N/S R. 27 E. Lyon County
PERMIT NO. M10 1347 (Issued by Water Resources) Parcel No. N/A Subdivision Name N/A

3. WORK PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☑ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☑ Other Auger

6. LITHOLOGIC LOG

Material	Water Stratn	From	To	Thickness
Surface Alkali, then Brown Clayey loam and Organics		0	2	2
Brown, fine Sandy loam		2	3½	1½
Black, fine sandy, friable Clay balls, (Not moist)		3½	5½	2
Brown, Slightly Moist Clay		5½	10	4½
Saturated, #3 Sand and pea grav.	10	10	21	11
Silty fine Sand		21	23	2
Silty Clay		23	25	2

RECEIVED MAR 18 AM 10 39 ENGINEERS OFFICE

Date started 3-15-05, 19
Date completed 3-15-05, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
GPS Location		
39 06 09.6		
118 55 42.4		
NAD 83	± 14	feet

8. WELL CONSTRUCTION
Depth Drilled 25 Feet Depth Cased 25 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
6 5/8 Inches	0 Feet	25 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2"	PVC	Sch 40	0	25
Flush Threads				

Perforations:
Type perforation Slot
Size perforation 0.020 inch
From 20 feet to 25 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 0 to 1
Placement Method: ☐ Pumped ☑ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☑ Concrete Grout

Gravel Packed: ☐ Yes ☑ No #3 Coarse Native Sand and Pea Grav.
From 7½ feet to 25 feet

9. WATER LEVEL
Static water level 5.64 feet below land surface
Artesian flow NO G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name R.N. Pennington (Contractor)
Address 333 W. Nye Lane (Contractor)
Carson City Nv 89706
Nevada contractor's license number issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller FP-1857
Signed R.N. Pennington (By driller performing actual drilling on site or contractor)
Date 3-18-05

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627