

(Poques well)

916602

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 7450  
Rec. Oct 30 1963  
Well No. \_\_\_\_\_  
Permit No. \_\_\_\_\_  
Do not fill in

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner Bureau of land management Driller J. R. Reynolds  
Address Elko Nev Address Wells Nevada Lic. No. 28  
Location of well: NE 1/4 SE 1/4 Sec 29, T30N/S, R55E, in Elko County \_\_\_\_\_  
or \_\_\_\_\_

Water will be used for NO water Total depth of well 499  
Size of drilled hole 6" Weight of casing per linear foot 18 lbs  
Thickness of casing .219 Temp. of water 9  
Diameter and length of casing 6" x 414 ft  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure NO  
If nonflowing well give depth of standing water from surface 313 ft

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well Sept 20-63 Date of completion of well Oct 12-63

Type of well rig Shure drill

## LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	38	38	Brown clay gravel.
38	41	3	Brown rock
41	48	7	Brown clay
48	51	3	Brown rock.
51	313	262	water in dirty gravel. (2 G.P.M.)
<del>313</del>	<del>320</del>	<del>7</del>	<del>Brown dirty gravel.</del>
313	320	7	Brown dirty gravel.
320	390	70	Brown clay & gravel.
390	407	17	white bentonite.
407	499	92	Brown sticky clay. Total depth 499.

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from \_\_\_\_\_ to \_\_\_\_\_ ft.

Other aquifers \_\_\_\_\_

First water at \_\_\_\_\_ feet.

Casing perforated

from \_\_\_\_\_ to \_\_\_\_\_ ft.

Size of perforations \_\_\_\_\_



