


22421

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



96642
Log No. 8668
Rec. May 12 1966
Well No.
Permit No. 22484
Do not fill in.

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner Hugh Tipton Driller Dave McNinch

Address Golconda, Nevada Address P.O. Box 585 Winn. Nev. Lic. No. 219

Location of well: NW 1/4 SE 1/4 Sec. 4, T.33. N/S, R. 40E, in Humboldt County

or N 40.761325 W 117.479836 NAD27 Basin 065

Water will be used for Irrigation Total depth of well 530'

Size of drilled hole 16" Weight of casing per linear foot 45#

Thickness of casing 1/4" Temp. of water Mild

Diameter and length of casing 16" OD x 247'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 120'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well Jan. 28, 1966 Date of completion of well March 28, 1966

Type of well rig #50 Keystone Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	40	40	Black soil
40	83	43	Dry gravel & clay
83	91	8	Fine gravel
91	117	26	Clay & gravel
117	140	23	Cemented gravel
140	153	13	Clean fine gravel
153	200	47	Clay with gravel seams
200	232	32	Clean gravel
232	334	102	Tight clay
334	340	6	Clean fine gravel
340	530	190	Clay with hard sand seams

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)

from 200 to 232 ft.

Other aquifers 140-153

First water at 140 feet.

Casing perforated

from 140 to 247 ft.

Size of perforations

3/8 x 2 1/4 slot



