SBO-3

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 96960
Permit No.
Basin 212

NOTICE OF INTENT NO. 22184

1. OWNER American Pacific Corporation
MAILING ADDRESS 3770 Howard Hughes Pkwy Suite 300 Las Vegas, NV 89109

ADDRESS AT WELL LOCATION Over Flow Parking Lot Between Weisner & Broadbent Henderson, Nevada

2. LOCATION NW ¼ NE ¼ Sec. 35 T. 21 N/S R. 62 E/W Clark County

PERMIT NO. (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other Sonic

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sand and Gravels with Variable Silt		0	3'	3'
Silty Sandy Gravel, Fine to Coarse up to 2"		3	11	8'
Sandy Gravel with trace Silt Dry to Slightly Damp		11	13	2
Sand Fine to Medium With Some Silt and Some fine Gravel, Wet, Dark Yellowish BN	✓	13	17	4
Caliche, Gravel Conglomerate		17	22	5
Muddy Creek Formation, Clayey Silt, Pale Greenish White,		22	23	1

LOCAL DWR RECEIVED APR 25 2005 LAS VEGAS OFFICE

Date started 9-14-04 Per Driller Phone, 19
Date completed 9-14-04, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 23 Feet Depth Cased 23 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
8 Inches	0 Feet	23 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.375	.70	.308	0	7

Perforations:
Type perforation Factory Slotted
Size perforation 0.020
From 7 feet to 22' feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 5'
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☒ Concrete Grout & Bentonite Chips
Gravel Packed: ☒ Yes ☐ No
From 23 feet to 5 feet

9. WATER LEVEL
Static water level ~~20~~ 16 feet below land surface
Artesian flow NO G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Phillip Camel Contractor Brent Longyear
Address 7773 W. Seldon Lane Contractor
Peoria, Arizona 85345
Nevada contractor's license number issued by the State Contractor's Board 0010157
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M2148
Signed Phillip E. Camel By driller performing actual drilling on site or contractor
Date 10-6-04

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627