WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 97033
Permit No.
Basin 065

NOTICE OF INTENT NO. 55186

1. OWNER Newmont Mining Corp
MAILING ADDRESS P.O. Box 3883
Valmy, NV 89438

ADDRESS AT WELL LOCATION 5 miles west of Valmy at the Lone Tree Mine

2. LOCATION SE ¼ NE ¼ Sec. 11 T. 34 (N) S R. ~~73~~ 42 E Humboldt County

PERMIT NO. | Issued by Water Resources | Parcel No. | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Siltstone		0	525	525
Valmy		525	925	400

Pumped through trimmie at 840' 4 sacks of Kwik Plug Fine for seal on sand. Then mixed 850 gal of water with 28 sacks of Super Plug slurry, pumped to static level. Poured 144 sacks of Kwik Plug 3/8's to bring up to 50' level for cement plug

RECEIVED 05 JUN 17 PM 2:04 STATE ENGINEERS OFFICE

Date started 6-4, 2005
Date completed 6-10, 2005

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 925 Feet Depth Cased 925 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
12 3/4 Inches	0 Feet	20 Feet
8 Inches	20 Feet	715 Feet
7 3/4 Inches	715 Feet	925 Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2"	PVC	Sch 80	0	925

Perforations:
Type perforation Slotted
Size perforation .020
From 855 feet to 915 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☐ Yes ☐ No
From 925 feet to 850 feet

9. WATER LEVEL
Static water level 649.5 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name EKlund Drilling Co (Contractor)
Address P.O. Box 2748 (Contractor)
Elko, NV. 89803
Nevada contractor's license number issued by the State Contractor's Board 0030823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-1769
Signed Warren Hartley (By driller performing actual drilling on site or contractor)
Date 6-10-05

(Rev. 12-01) USE ADDITIONAL SHEETS IF NECESSARY (O)-627