WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 97067
Permit No.
Basin 066

NOTICE OF INTENT NO. 26560

1. OWNER ATNA RESOURCES
MAILING ADDRESS PO BOX 969 WINNEMUCCA NEV
ADDRESS AT WELL LOCATION PINSON MINE SITE

2. LOCATION S/E ¼ S/E ¼ Sec. 29 T 38 N N/S R 42 E E Humbolt County
PERMIT NO. M/01354 (Issued by Water Resources) 0712107 (Parcel No.) Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Conglomerate/Calc Silicate	58'	0	56	56
Limestone - Fracture		56	97	41
Blk Shale		97	178	81
Sparry & Shale		178	290	112
White/Tan Sparry		290	318	28
Blk Shale		318	363	45
Limestone - Fracture		363	387	14
Tan/Pink Limestone		387	418	31
Marble		418	487	69
S/S & Shale		487	505	18
Marble		505	521	16
Skarn		521	536	15
Marble		536	582	46
Limeston & Blk Shale		582	643	61
Limestone		643	915	272
Limestone & Blk Shale		915	960	45

Date started 5-10, 2005
Date completed 5-24, 2005

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
	N/A	

8. WELL CONSTRUCTION
Depth Drilled 960' Feet Depth Cased 960' Feet

HOLE DIAMETER (BIT SIZE)

	From	To
6 3/4 Inches	0 Feet	960 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2½		SCH 40	0	960

Perforations:
Type perforation slot
Size perforation .020
From 900 feet to 960 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 875
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 875 feet to 960 feet

9. WATER LEVEL
Static water level 53' feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name LAYNE CHRISTENSEN CO. (Contractor)
Address 11001 ETIWANDA AVE (Contractor)
FONTANA CA. 92337
Nevada contractor's license number issued by the State Contractor's Board 0019161
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1682
Signed [signature] By driller performing actual drilling on site or contractor
Date 6-7-05

(Rev. 12-01) USE ADDITIONAL SHEETS IF NECESSARY (O)-627