


STATE OF NEVADA  
 DIVISION OF WATER RESOURCES  
**WELL DRILLER'S REPORT**

97181  
 OFFICE USE ONLY



PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

Log No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
 Basin 05  
 NOTICE OF INTENT NO. 55081

1. OWNER PTP INC  
 MAILING ADDRESS P.O. BOX 188  
MINDEN, NV 89423

ADDRESS AT WELL LOCATION 175 HWY 395,  
GARDNERVILLE, NV 89410 (HOLE # B-4)  
 County DOUGLAS  
 Subdivision Name PINE VIEW ESTATES

2. LOCATION NE 1/4 NE 1/4 Sec. 5 T 11N  
 PERMIT NO. EPA #NV504000001 Issued by Water Resources  
BIA LAND Parcel No.

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other

4. PROPOSED USE  
 Domestic  Municipal/Industrial  
 Irrigation  Monitor  
 Test  Stock

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
<u>BROWN CLAY &amp; ROCK</u>		<u>0</u>	<u>50</u>	<u>50</u>
<u>#10-20 COLORADO SILICA SAND WAS TREMIED FROM 50' TO 38' - #8 GRANULAR BENTONITE TREMIED FROM 38' TO 35' - PUMPED ABANDONITE FROM 35' TO 7' - POURED NEAT CEMENT FROM 7' TO SURFACE &amp; PLACED A 22" X 22" X 3.5" CEMENT PAD AROUND A 6" X 8" STEEL LOCKING MONUMENT WITH A 4" PVC LOCK CAP - 4" THREADED CAP WAS PLACED ON THE BOTTOM OF THE 4" PVC</u>				

8. WELL CONSTRUCTION

Depth Drilled 50 Feet Depth Cased 50 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From	To	Feet
<u>10.5</u>	<u>0</u>	<u>50</u>	<u>50</u>

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>4.5</u>		<u>SCH 40</u>	<u>+5</u>	<u>50</u>

Perforations:  
 Type perforation MACHINE SLOT IN ASTM F 480 SCH 40  
 Size perforation .010

From	To	Feet
<u>40</u>	<u>50</u>	<u>10</u>

Surface Seal:  Yes  No  
 Depth of Seal 38  
 Placement Method:  Pumped  Poured  
 Gravel Packed:  Yes  No  
 From 38 feet to 50 feet

Seal Type:  
 Neat Cement  
 Cement Grout  
 Concrete Grout

Date started 4/1/2005 19\_\_\_\_  
 Date completed 4/1/2005 19\_\_\_\_

7. WELL TEST DATA

TEST METHOD:	Bailer	Pump	<input checked="" type="checkbox"/> Air Lift
G.P.M.	Draw Down (Feet Below Static)	Time (Hours)	

9. WATER LEVEL  
 Static water level DRY HOLE feet below land surface  
 Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
 Water temperature \_\_\_\_\_ °F Quality \_\_\_\_\_

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name HACKWORTH DRILLING, INC Contractor  
 Address P.O. BOX 850 Contractor  
ELKO, NV 89803  
 Nevada contractor's license number issued by the State Contractor's Board 020582  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1998  
 Signed Bradley D. Wise  
 By driller performing actual drilling on-site or contractor  
 Date 4/5/2005