COPIES TO
- DIVISION OF WATER RESOURCES
- CLIENT'S COPY
- WELL DRILLER'S COPY

PRINT OR TYPE ONLY

STATE OF NEVADA

DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 97247
Permit No.
Basin 085
NOTICE OF INTENT NO. 39903

1. OWNER Nick Brown
MAILING ADDRESS 3040 Pershing Ln
Reno, NV

ADDRESS AT WELL LOCATION
3040 Pershing Ln
Reno, NV

2. LOCATION NE ¼ NE ¼ Sec 6 T 16 N R 20 E Washoe County

PERMIT NO. N/A (Issued by Water Resources) | 050-424-05 (Parcel No.) | Subdivision Name

3. WORK PERFORMED
☐ New Well ☒ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other Mud

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Dark brown sand		0	17	17
light brown course sand,		17		
gravel			21	4
light brown sandy clay		21	25	3
light brown course sand		25	47	22
light sandy brown clay		47	50	3
light brown course sand		50	73	23
gray clay		73	77	4
light brown course sand		77	125	48
conglomerate		125	176	51
light course sand		176	200	24
light brown course sand,		200		
gravel			217	17
old well was plugged by an				
attempt to pull casing,				
casing was perforated				
from 62' back to 45' and				
cement was pumped				
through tremmie pipe				
from 62' to surface				

Date started 12-18, 20 04
Date completed 5-4, 20 05

7. WELL TEST DATE

TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
Approx	20	200	2

8. WELL CONSTRUCTION
Depth Drilled 217 Feet Depth Cased 217 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
10 Inches	0 Feet	217 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8"steel	17	.250	-1	17
6 5/8"PVC	4.95	.390"	17	217

Perforations:
Type perforation Mill Slot
Size perforation .030
From 97 feet to 117 feet
From 177 feet to 197 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 80
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout
Gravel Packed: ☒ Yes ☐ No
From 80 feet to 217 feet

9. WATER LEVEL
Static water level 52 feet below land surface
Artesian flow none G.P.M none P.S.I
Water temperature cool °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name MILLER & SONS DRILLING C0. (CONTRACTOR)
Address P.O. Box 8056 (CONTRACTOR)
Reno, NV 89507
Nevada contractor's license number issued by the State Contractor's Board 037915
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1418
Signed Bruce Miller
By driller performing actual drilling on site or contractor
Date 6-2-05

Forms Provided by Forms-On-A-Disk, Inc. · (214) 340-9429 · FormsOnADisk.com