WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 97812
Permit No.
Basin Ø66

NOTICE OF INTENT NO. 55209

1. OWNER Newmont mining Corp
MAILING ADDRESS P.O. Box 388
Velmy, NV 89438

ADDRESS AT WELL LOCATION Twin Creeks mine
Golconda, NV

2. LOCATION SE ¼ SW ¼ Sec. 30 T. 39 N/S R. 43 E. Humboldt County

PERMIT NO. Issued by Water Resources | Parcel No. | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☐ Air ☐ Other

6. M/030-38B LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Alluvium till 740'				
Set 1240' of Casing in hole 4" nominal				
Trimmy in 3½ yrds gravel				
Pump in Abandonite to 50'				
Pour in 50' Cement Seal				
Set 8" monument and Cap and Develope well until Clean				

RECEIVED
05 AUG 26 AM 11:33
STATE ENGINEERS OFFICE

Date started 6/28, 2005
Date complated 7/20, 2005

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
30-40		

8. WELL CONSTRUCTION
Depth Drilled 1255 Feet Depth Cased ~~1240~~ 1237' Feet

HOLE DIAMETER (BIT SIZE)
8¾ Inches From 0 Feet To 1255 Feet
Inches Feet Feet
Inches Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4½		¼	~~0~~	~~1240~~
			+3	1237

Perforations:
Type perforation Slot
Size perforation ~~[illegible]~~ 1/8"
From 1220 feet to 1020 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50'
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 1240 feet to 1018 feet

9. WATER LEVEL
Static water level 439 feet below land surface
Artesian flow — G.P.M. — P.S.I.
Water temperature — °F Quality Good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Co
Contractor
Address P.O. Box 2748
Contractor
Elko, NV 89803
Nevada contractor's license number issued by the State Contractor's Board 0030823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2089
Signed [signature]
By driller performing actual drilling on site or contractor
Date 7/20/05

(Rev. 12-01) USE ADDITIONAL SHEETS IF NECESSARY (O)-627