

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT
 Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 28613

1. OWNER JACK STANT (SCE) ADDRESS AT WELL LOCATION 655 BRUCE WOODBURY DR
 MAILING ADDRESS 655 BRUCE WOODBURY DR LAUGHLIN NEV 89029
 2. LOCATION S/W 1/4 NW 1/4 Sec 24 T. 32.5 N/S R. 66 E CLARK County
 PERMIT NO. 66551E 264-32-000-091 Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other.....
 4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
 5. WELL TYPE
 Cable Rotary RVC
 Air Other.....

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thick-ness |
|-------------------|--------------|------|----|------------|
| WAIVER # R-1305 | | | | |
| WELL ABANDONMENT | | | | |
| INFORMATION ON | | | | |
| ATTACHED LETTER | | | | |
| DCNR/DWR RECEIVED | | | | |
| DEC 12 2005 | | | | |
| LAS VEGAS OFFICE | | | | |

8. WELL CONSTRUCTION
 Depth Drilled.....Feet Depth Cased.....Feet
 HOLE DIAMETER (BIT SIZE)
 From To
Inches.....Feet.....Feet
Inches.....Feet.....Feet
Inches.....Feet.....Feet

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|--------------------|---------------------|-------------------------|-------------|-----------|
| | | | | |

Perforations:
 Type perforation.....
 Size perforation.....
 From.....feet to.....feet
 From.....feet to.....feet
 From.....feet to.....feet
 From.....feet to.....feet
 From.....feet to.....feet

Surface Seal: Yes No Seal Type:
 Neat Cement
 Cement Grout
 Concrete Grout
 Placement Method: Pumped
 Poured
 Gravel Packed: Yes No
 From.....feet to.....feet

9. WATER LEVEL
 Static water level.....feet below land surface
 Artesian flow.....G.P.M.....P.S.I.
 Water temperature.....°F Quality.....

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name LAYNE CHRISTENSEN Co. Contractor
 Address 11001 ETIWAANDA AVE Contractor
FONTANA CA. 92337
 Nevada contractor's license number issued by the State Contractor's Board 0019101
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1682
 Signed.....
 By driller performing actual drilling on site or contractor
 Date 12-2-05

Date started 11-11, 2005
 Date completed 12-1-05, 2005

7. WELL TEST DATA

| TEST METHOD: | G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|--------|-------------------------------|--------------|
| <input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift | | | |
| | | | |
| | | | |
| | | | |
| | | | |

On November 11, 2005 we attempted to fish out pump, hose and wire from a 6" well using an Orange Peel Fishing Tool. We managed to retrieve all of the pump wire out of the well. We had no success with hose and pump after spending numerous hours of running tools. We then attempted drilling out with Drag bit but because of the severe curvature of the well casing, we could not pass 78' without further damage to the well.

After submitting a variance to request a waiver to abandon well, we pressure pumped neat cement through an existing 2" sounding tube constructed in the same bore-hole open to bottom. It took (56) ninety-four pound bags of cement before more could be installed.

The following morning we ran 80' of trimmie in the 6' well from the top and pumped (49) ninety-four pound bags of cement to bring to surface.

The following morning we excavated 5' below ground level with Back-Hoe and placed a 2x4 concrete dome on to well casing and later back filled with native soil.

DCNR/DWR
RECEIVED

DEC 12 2005

LAS VEGAS OFFICE