STATE OF NEVADA * Revised Log *
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 98703
Permit No.
Basin 062

NOTICE OF INTENT NO. 54243

1. OWNER Newmont Mining Corp.
MAILING ADDRESS PO Box 669
Carlin, NV 89822

ADDRESS AT WELL LOCATION
IVANHOE MINE
WW-4

2. LOCATION NE 1/4 ~~NE~~ SE 1/4 Sec. 5 T 37 N/S R 48 E ELKO County
PERMIT #52753 Permit Cancelled in 1999
Issued By Water Resources

Parcel No.

Subdivision Name

3. WORK PERFORMED
[ ] New Well [ ] Replace [ ] Recondition
[ ] Deepen [X] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[X] Municipal/Indus [ ] Monitor [ ] Shock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Perforated casing from 60 feet to 200 feet				
and 340 feet to 460 feet with hole				
air perforator				
Set 2 7/8" tremie pipe to 740 feet				
Pumped neat cement 253 sacks, 1250				
gallons water and retarded from bottom up				
Cement was 120% calculated volumn				

Date Started July 31 2005
Date Completed July 31 2005

7. WELL TEST DATA
TEST METHOD :
[ ] BAILER [x] PUMP [ ] AIR LIFT

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 748 Feet Depth Cased 748 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
14 3/4	Inches	0	Feet	72	Feet
12 1/4	Inches	72	Feet	748	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (inches)	Weight (pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8 5/8		0.250	+1	748

Type Perforation Mill Slot & Wire Wrap
Size Perforation 0.080

From	200	feet to	340	feet
From	460	feet to	748	feet
From		feet to		feet
From		feet to		feet

Surface Seal : [x] Yes [ ] No
Seal Type : [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout
Depth of Seal 60 feet
Placement Method : [ ] Pumped [ ] Poured
Gravel Packed : [ ] Yes [ ] No

From	60	feet to	748	feet
From		feet to		feet

9. WATER LEVEL
Static Water Level 209 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Hydro Resources Nevada Inc. dba Humboldt Drilling and Pump Co.
Address 4975 West Winnemucca Boulevard
Winnemucca, Nevada 89445

NV Contractor's LIC# issued by the State Contractor's Board 56797
NV Driller's LIC# issued by Div. of Water Resources, on-site driller 2099

Signed : C. Jaynes Office Date : 9/9/05