

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT



OFFICE USE ONLY
Log No. 99215
Permit No. _____
Basin 084

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 55502

1. OWNER Double P Farms-Tom Pratt
MAILING ADDRESS 6105 Whiskey Springs Rd.
Reno, NV 89510

ADDRESS AT WELL LOCATION
19001 Pyramid Lake Hwy. Sparks, NV 89436
Well #3

2. LOCATION SE 1/4 SW 1/4 Sec. 5 T 22 N/S R 21 E Washoe County
PERMIT NO. 53304, 53306 077-090-13
WL #050292 Issued By Water Resources Parcel No. _____ Subdivision Name _____

3. WORK PERFORMED
 New Well Replace Recondition Deepen Abandon Other
4. PROPOSED USE
 Domestic Irrigation Test Monitor Shock Municipal/Industrial Other
5. WELL TYPE
 Cable Rotary RVC Air Other

6. LITHOLOGIC LOG

Material	From	To	Thickness
Sand	0	14	14
Coarse sands and some small gravels	14	48	34
Clay	48	55	7
Coarse sands	55	130	75
Coarse sand & clay	130	145	15
Coarse sands	145	186	41
Coarse sand, gravel and rocks	186	190	4
Coarse sand & clay	190	240	50
Clay	240	246	6
Clay and sand	246	253	7
Sand and gravels	253	305	52
Sand and clay	305	315	10
Coarse sand & some gravel	315	364	49
Clay & sand layers	364	376	12
Sand & gravel w/clay layers	376	379	3
Clay	379	404	25
Sand & gravel w/clay layers	404	408	4
Clay w/coarse sands	408	426	18
Sand & gravel w/clay layers	426	464	38
Clay w/some sand streaks	464	514	50
Sand and gravel	514	526	12
Clay w/sand streaks	526	537	11
Sand and clay layers	537	555	18
Sand & gravel w/small clay layers	555	610	55
Clay and sand	610	649	39
Clay w/sand & small gravels	649	669	20
Sand & small gravel w/clay layers	669	707	38
Clay w/sand stringers	707	723	16
Sand & gravel w/clay layers	723	780	57
Sandy clays w/some gravel	780	810	30

8. WELL CONSTRUCTION
Depth Drilled 810 Feet Depth Cased 800 Feet
HOLE DIAMETER (BIT SIZE)
From 0 To 50
36 Inches 0 Feet 50 Feet
24 Inches 50 Feet 810 Feet
Inches Feet Feet Feet
CASING SCHEDULE

Size O.D. (inches)	Weight (pounds)	Wall Thickness (inches)	From (Feet)	To (Feet)
30		Blank .250	0	5
30		Corrugated	5	45
30		Blank .250	45	50
16		Blank .250	+2	200

Type Perforation _____ Mill Slot Double Row
Size Perforation 0.090
From 200 feet to 800 feet
From _____ feet to _____ feet
From _____ feet to _____ feet
From _____ feet to _____ feet
Surface Seal: Yes No Seal Type
Depth of Seal 50' Neat Cement Cement Grout Concrete Grout
Placement Method: Pumped Poured
Gravel Packed: Yes No
From GL feet to 810 feet
From _____ feet to _____ feet

9. WATER LEVEL
Static Water Level 178.7 feet below land surface
Artesian flow _____ G.P.M. _____ P.S.I.
Water temperature Cool F Quality Good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Date Started 11/10 2005
Date Completed 11/13 2005

Name Hydro Resources Nevada Inc. dba. Humboldt Drilling and Pump Co.

7. WELL TEST DATA

Address 4975 West Winnemucca Boulevard

TEST METHOD: BAILER PUMP AIR LIFT

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
Pumping Level 215'	2,000	36.3	2

Winnemucca, Nevada 89445
NV Contractor's LIC# issued by the State Contractor's Board 56797
NV Driller's LIC# issued by Div. of Water Resources, on-site driller 2177
Signed: C. Jaynes - Office Date: 12/7/05